



| OV or GND = RF OFF +5V or NC = RF OFF | _ | 9 |
|---|-----|---------|
| Over Temperature Flag 0V = Temperature Fault +5V = No Fault | 0 | 7 |
| Ground | - | 1,2,6,8 |
| DC Power (+28 Volts) | _ | 3,4,5 |
| Function | 0/0 | Pin# |
| Pinout | | |

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED. UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS



FMAM5080 V002162YYYYMMDDXXXX

Fairview Microwave
an INFINIT® brand
www.fairviewmicrowave.com

LABEL

an INFINIT® brand

TIT IE



A | | CAGE CODE 3FKR5 DRAWN BY
K.DANG ITEM NO. FMAM5080

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

N/A

REV

 $... X = \pm .2$ [5.08] $... X = \pm .02$ [.51] $... X = \pm .005$ [.13]

FRACTIONS ± 1/32 ANGLES ± 1°

L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1624] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5%L / -0

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICHOWAVE CORPORATION.
ALL RIGHTS RESERVED.

NGLE PROJECTION

TOLERANCES:

CABLE LENGTH (L) TOLERANCES: