



.52 [13.1]

1.20

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

* WICCOMAND

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES

DIMENSIONS IN [] ARE MILLIMETERS.



TITLE

				ė
		××× ××× ××× ××× ××× ××× ××× ××× ××× ××		UN
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	TOLERANCES: ±.2 [5.08] FRACTIONS ±.02 [.51] ± 1/32 ±.005[.13] ANGLES ± 1		TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
	_		CABLE LENGTH (L	WISE SPECIFIED LEADING DIMENSION DIMENSIONS IN [] ARE MILLIMETERS
		[305] = +1 [25] / -0 1524] = +2 [51] / -0 3048] = +4 [102] / -0) TOLERANCES:	NS ARE INCHES
SCALE N/A	SHEET OF 1	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATIO ALL RIGHTS RESERVED.	THE INFORMATION AND	THIRD-ANGLE PROJECTION
	SCALE	120 3048 < L < 300 (7620) = +6 [152] / -0	[25]/-0 [51]/-0 [102]/-0 [152]/-0 SHEE %L/-0 SCAL	CABLELENGTH (L) TOLERANCES: L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 100 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0 WIN ARE FOR REFERENCE ONLY.