

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO US LAW PROHIBITED.

The diagram illustrates a coaxial cable assembly. It features two crimped connectors at the top and bottom. Between the connectors, there are two sections of heat shrink tubing, each labeled "2X HEAT SHRINK SLEEVE". The total length of the cable is indicated by a dimension line labeled "LENGTH MEASURED FROM CONTACT TO CONTACT". The text "LMR-400" is also present, likely referring to the type of coaxial cable used.

ביקור

בוגר מילדי

## CONTACT

UNLESS OTHERWISE SPECIFIED, LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [ ] ARE MILLIMETERS				THIRD-ANGLE PROJECTION
TOLERANCES:				CABLE LENGTH (L) TOLERANCES:
X = $\pm 2.2$ [5.08] FRACTIONS XX = $\pm 0.2$ [5.1] $\pm 132$				12 [305] < L < 12 [305] = $\pm 2.2$ [5.1] - 0
XXX = $\pm 0.05$ [1.3]	ANGLES $\pm 1^\circ$			60 [1524] < L < 120 [3048] = $\pm 4.4$ [102] - 0
				120 [3048] < L < 300 [7620] = $\pm 6.0$ [152] - 0
				300 [7620] < L = $\pm 9.0$ [228] - 0
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.				SCALE
SIZE A	CAGE CODE 3FKR5	DRAWN BY K.DANG	ITEM NO. FMC00405	REV A
N/A				
 THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROTRON CORPORATION. ALL RIGHTS RESERVED.				