

NOTES:

SMA MALE

BNC MALE

: CABLES 36" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END 6.0" FROM THE END OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS, DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

7 MICTORIAN OF THE WITH THE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT UNITED STATES OF THE WISE SPECIFIED LEADING DIMENSIONS ARE INCHES OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES OTHERWISE



TITLE

⊳	SIZE		X = ±.2 [5.08] FRACTIONS XX = ±.02 [.51] ± 1/32 XXX = ±.005[.13] ANGLES ± 1°			TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
3FKR5	CAGE CODE	ALL DIME					
R5		OHS SNOISN	FRACTIONS ± 1/32 ANGLES ± 1°				
K.DANG	DRAWN BY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	L ≤ 1. 12 [305] < L ≤ 60 60 [1524] < L ≤ 120 120 [3048] < L ≤ 300 300 [76			CABLE LENGTH (L) TOLERANCES	
FMC00498	ITEM NO.	NCE ONLY.	L ≤ 12 [305] = +1 [25] / 0 12 [305] < L ≤ 50 [1524] = +2 [51] / 0 60 [1524] < L ≤ 120 [3048] = +4 [102] / 0 120 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0			L) TOLERANCES:	ONS ARE INCHES
		SCALE N.	SHEET 1 O	THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRNEW MICROWAVE CORPOPATION. ALL HOHITS RESERVED.			
⊳	REV	N/A	1				OJECTION