



## NOTES:

1. CABLES 84" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 84" HAVE 2 LABELS, ONE AT EACH END
12.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.





D OKE	9719				
3FK	ALL DIMI	JUS[.13]	$X = \pm .2$ [5.08] $XX = \pm .02$ [.51]	TOLERANCES:	  -  -
ת אל	ENSIONS SHO	X = ±.2 [5.08] FRACTIONS XX = ±.02 [.51] ±.132 XXX = ±.005[.13] ANGLES ± 1°		NCES:	DIMENSIONS
MVFFRAPPAN	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	_	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0	CABLE LENGTH (L) TOLERANCES	DIMENSIONS IN [] ARE MILLIMETERS
ITEM NO. FMCA2415	NCE ONLY.	120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0	L) TOLERANCES:	AZE NCHEO	
	SCALE N	SHEET 1 C	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION ALL RIGHTS RESERVED.	THE INFORMATION AND	<b>+</b>
<b>D</b>	N/A	TON AND DOCUMENT ERTY OF ECORPORATION. ESERVED. DF 1			+

T-Rev.