



Ø.63
[15.9]
MIN.

.53
MOUNTING HOLE

NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT
ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.
UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



III III III

⊳	SIZE		$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		TOLERANCES: CABLE LENGTH (L) TOLERANCES:	ONLESS OF HERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES
3FKR5	CAGE CODE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY				
MVEERAPPAN	DRAWN BY					
FMCA2737	ITEM NO.	NCE ONLY.	CABLE LENGTH (L.) TOLERANCES: L ≤ 12 [3065] < L ≤ 60 [1824] + 2 [51] / -0 12 [305] < L ≤ 100 [3048] = +4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0 SHEET			ON ARE INCHES
		SCALE N/A	HE INFORMATI SIGN IN THIS DISTRIBUTION OF THE PROPE WINDEROWAVE WINDEROWAVE			+
⊳	REV	Ά	1	OCUMENT RTY OF CORPORATION. SERVED.	ON AND	