



NOTES:

CABLES 36" AND UNDER HAVE 1 LABEL CENTERED. CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END 6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED. UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

A		UNLESS OTHE TOLER X = ±.2 [5.08] .XX = ±.02 [.51] .XXX = ±.005[.13]
CAGE CODE 3FK	ALL DIME	UNLESS OTHERWISE DIMEN TOLERANCES X = ±.2 [5.08] FRAC X = ±.02 [51] ± X = ±.005[.13] ANG
3FKR5	NSIONS SH	INCES: FRACTIONS ± 1/32 ANGLES ± 1°
MVEER	OWN ARE	CAE
MVEERAPPAN	FOR REFER	WISE SPECIFIED LEADING DIMENSIONS IN [] ARE MILLIMETERS DIMENSIONS IN [] ARE MILLIMETERS CABLE LENGTH (L. 12.005] < L. 2.60 [12.204] < L. 2.60 [12.204] < L. 2.00 [
ITEM NO.	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN 1 ARE MILLMETTERS TOLERANCES: CABLE LENGTH (L) TOLERANCES: L = 12 [205] - 4 (= ±.2 [5.08] FRACTIONS 12 [305] - L = 50 [15.24] + 2 [51] / -0 (= ±.02 [.51]
FMCA2784	SCALE Z	THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRNEW MICROWAVE CORPORATION ALL RIGHT'S RESERVED. SHEET 1 OF 1
A REV	N/A	TON AND SOCUMENT RTY OF SCREWED. SERVED. JF 1

A