



NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

A SIZE		UNLESS OTHEI TOLER X = ±.2 [5.08] .X = ±.02 [.51] .XX = ±.005[.13]
CAGE CODE 3FKR5	ALL DIME	SS OTHERWISE: DIMEN TOLERANCES: [5.08] FRAC [5.08] FRAC [5.13] ANG
R5	NSIONS SHO	WISE SPECIF DIMENSIONS NCES: FRACTIONS ± 1/32 ANGLES ± 1°
PSRINIVAS	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	
FMCA2792	NCE ONLY.	LEADING DIMENSIONS ARE INCHES] ARE MILLIMETERS CABLE LENGTH (L) TOLERANCES: L ≤ 12 [365] = +1 [25] / 0 12 [305] < L ≤ 60 [1524] = +2 [31] / 0 80 [1524] < L ≤ 120 [3048] = +4 [102] / 0 20 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0
\2792	SCALE N	THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE REPORT OF FAIRNER MAIGROWAVE CORPORATION ALL RIGHTS RESERVED. SHEET 1 OF 1
A REV	N/A	PROJECTION ATTION AND DOCUMENT DOCUMENT ECRITY OF ECRIT