



NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



TITLE

A		UNLES . X = ±.2 .XX = ±.02 .XXX = ±.00
3FKR5	ALL DIMENSIONS SHO	S OTHER
PSRINIVAS	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	<u>Z</u> E
FMCA2846	NCE ONLY.	LEADING DIMENSIONS ARE INCHES] ARE MILLIMETERS CABLE LENGTH (L) TOLERANCES: L ≤ 12 [365] = ±1 [25] / -0 12 [305] < L ≤ 60 [1524] = ±2 [51] / -0 80 [1524] < L ≤ 120 [3048] = ±4 [102] / -0 20 [3048] < L ≤ 300 [7620] = ±6 [152] / -0 300 [7620] < L = ±5%L / -0
	SCALE N.	THIRDANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRNEW MICROWAVE CORPORATION ALL RIGHTS RESERVED. SHEET 1 OF 1
A REV	N/A	ROJECTION TION AND DOCUMENT ERRYY OF E CORPORATION. EESERVED. OF 1