



NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

A		XX = ±	×     +		UNL
CAGE CODE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	.X = ±.2 [5.08] .XX = ±.02 [.51] .XXX = ±.005[.13]		TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
3FKR5		FRACTIONS ± 1/32 ANGLES ± 1			
PSRINIVAS	OWN ARE FO	-		CABLE LENGTH (L) TOLERANCES:	
NIVAS	OR REFERE				
ITEM NO. FMC.	NCE ONLY.	16 (1524) < L < 120 (1024) = +4 (102) / -0 60 (1524) < L < 120 (3048) = +4 (102) / -0 120 (3048) < L < 300 (7620) = +6 (152) / -0 300 (7620) < L = +5%L / -0	L ≤ 12 [305] = +1 [25] / -0	L) TOLERANCES:	NS ARE INCHES
FMCA2875	SCALE N	THIRD-ANGLE PROJECTION  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPOPATION ALL RIGHTS RESERVED.  SHEET  1  1  THIRD-ANGLE PROJECTION  THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE ROPERTY OF FAIRVIEW MICROWAVE CORPOPATION  SHEET  1  1  THRO-ANGLE PROJECTION  THRO-ANGLE PRO			
A REV	N/A	ECORPORATION. ESERVED.  DF  1	TION AND DOCUMENT RTY OF		OJECTION