



NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

| A | | XXX = # XXX = # |
|------------------|--|---|
| CAGE CODE 3FK | ALL DIN | UNLESS OTHERWISE DME1 |
| R5 | MENSIONS SHO | UNLESS OTHERWISE SPECIFICIMENSIONS TOLERANCES: X = ±.2 [5.08] FRACTIONS XX = ±.02 [.51] ± 1/32 XXX = ±.005[.13] ANGLES ± f |
| PSRINIVAS | ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. | Z 🖺 |
| FMCA2924 | NCE ONLY. | DLEADING DIMENSIONS ARE INCHES [] ARE MILLIMETERS CABLE LENGTH (L) TOLERANCES: L ≤ 12 [306] = +1 [25] / 0 12 [305] < L ≤ 60 [1824] = +2 [51] / 0 60 [1824] < L ≤ 120 [3048] = +4 [102] / 0 120 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0 |
| 12924 | SCALE N | THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FARRYEEM WIGGOWAVE CORPORATION ALL RIGHTS RESERVED. SHEET 1 OF 1 |
| A REV | N/A | COLECTION TON AND DOCUMENT COMPODRATION. SERVED. JF 1 |