



NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



TITLE

SIZE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	X=±.2 [5.08] FRACTIONS 12 [305] < L ≤ 60 XX=±.02 [.51] ± 1/32 60 [1524] < L ≤ 120 XXX=±.005 [.13] ANGLES ± 1° 120 [3048] < L ≤ 300 300 [76:			TOLERANCES:	DIMENSIONS IN [] ARE MILLIMETERS
CAGE CODE						
ITEM NO.					NCE ONLY.	CABLE LENGTH (L.) TOLERANCES: L \$ 12 [305] = +1 [25] -0 12 [305] < L \$ 60 [1824] = +2 [51] /-0 60 [1524] < L \$ 120 [3048] = +4 [102] /-0 120 [3048] < L \$ 300 [7820] = +6 [182] /-0 300 [7820] < L = +5%L /-0
2027	SCALE N/A	THE INFORMATION AND DESIGNAN THIS DOCUMENT IS THE REPORT OF FAIRNEMANGROWANE CORPORATION ALL RIGHTS RESERVED. SHEET 1 OF 1				₽
REV >		1	CORPORATION. SERVED.	OCUMENT	4	