





NOTES:

1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



III III III

A). ± = XXX	XX = +		UNLE
CAGE CODE 3FK	ALL DIM	X=±.2 [5.08] FRACTIONS XX=±.02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1°		TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
3FKR5	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY			NCES:	
DRAWN BY	HOWN A			lo.	SIN[]A
DRAWN BY VTHANGARAJ	RE FOR F	L ≤ 12 [305] = +1 [25] / 0 12 [305] < L ≤ 60 [1524] = +2 [51] / 0 60 [1524] < L ≤ 120 [3048] = +4 [102] / 0 20 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0		CABLELE	RE MILLI
	REFEREN	1 ≤ 300 [200 [7620]	L≤12 <l≤60[<l≤120[< td=""><td>:NGTH (L</td><td>MENSION METERS</td></l≤120[<></l≤60[:NGTH (L	MENSION METERS
ITEM NO.	CE ONLY	L \(\) 300 [7620] \(\) L \(\) +6 [152] / 300 [7620] \(\) L \(\) +5%L / -0	$L \le 12 [305] = +1 [25] / -0$ $12 [305] < L \le 60 [1524] = +2 [51] / -0$ [1524] < 120 [3048] = +4 [193] / 0	CABLE LENGTH (L) TOLERANCES	NS ARE II
FMC,		$120 [3048] < L \le 300 [7620] = +6 [152] / -0$ $300 [7620] = +6 [152] / -0$	[25]/-0 2[51]/-0	NCES:	ICHES
FMCA3093	SCALE	SHEET	FAIRVIEV	,	7
		OF	IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION	THE INFORMATION AND	THIRD-ANGLE PROJECTION
REV	N/A	OF	OPERTY OF	MATION AN	T-PROJECT
≻			ORATION.	١٥	<u>N</u>