





MOUNTING HOLES

NOTES:

CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



III III III

A		UNLESS OTHE TOLER X = ±.2 [5.08] .X = ±.02 [.51] .XX = ±.005[.13]
3FKR5	ALL DIME	UNLESS OTHERWISE DME1
R5	OHS SNOISP	WISE SPECIFI DIMENSIONS NCES: FRACTIONS ± 1/32 ANGLES ± 1°
VTHANGARAJ	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS TOLERANCES: CABLE LENGTH (L) TOLERANCES: L ≤ 12 [5.08] FRACTIONS (= ±.02 [5.1] ± 1/32 00 [1524] < L ≤ 120 [3048] = +2 [51] /-0 00 [1524] < L ≤ 120 [3048] = +4 [102] /-0 00 [1524] < L ≤ 300 [7620] = +6 [152] /-0 300 [7620] < L = +5%L /-0 300 [7620] < L = +5%L /-0
FMCA3094	NCE ONLY.	ADING DIMENSIONS ARE INCHES RE MILLIMETERS 2ABLE LENGTH (L.) TOLERANCES: L ≤ 12 [305] = 41 [25] / -0 12 [305] < L ≤ 60 [1824] = +2 [51] / -0 [1824] < L ≤ 120 [3048] = +4 [102] / -0 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7820] < L = +5%L / -0
\3094	SCALE Z	THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGNAIN THIS DOCUMENT IS THE REPORTED TO ALL RIGHTS RESERVED. SHEET 1 OF 1
A	N/A	PROJECTION ATTION AND S DOCUMENT S ERTY OF PERTY OF PERT

A