



NOTES:

CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS



TITLE

Þ	SIZE			× == + >>		UNLE		
3F	CAGE CODE	ALL DIM	1000	2 [5.08]	TOLERANCES	SS OTHER		
3FKR5	Œ	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	FRACTIONS ± 1/32 ANGLES ± 1°			NCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS	
YTH.	DRAWN BY	HOWN AF	_				IFIED LE	
VTHANGARAJ	N BY	RE FOR RI	12 [305] < [1524] < 1 [3048] < 1			ABLE LE	ADING DI	
RA		120 L ≤ 300 300 [762			L ≤ 12	NGTH (L	MENSIO	
FMC	ITEM NO	ICE ONLY	L ≤ 12 [305] = +1 [25] / 0 12 [305] < L ≤ 60 [1524] = +2 [51] / 0 [1524] < L ≤ 120 [3048] = +4 [102] / 4 [3048] < L ≤ 300 [7620] = +6 [152] / 4 300 [7620] < L = +5%L / -0			CABLE LENGTH (L) TOLERANCES	NS ARE II	
		.`	JARE MILLMETERS CABLE LENGTH (L) TOLERANCES: CABLE LENGTH (L) TOLERANCES: L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 12 [304] < L ≤ 120 [3048] = +4 [102] / -0 12 [3048] < L ≤ 120 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0					
FMCA3098		SCALE	SHEET	FAIRVIE	0		1	
,			_	THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE INFORMATION AND DESIGN IN THIS DOCUMENT AIRWING MICROWAVIE CORPORATION ALL RIGHTS RESERVED. SHEET OF				
	REV	N/A	유	AVE COI	HS DOCU	MATION		
Þ	Ϋ́		_	ECTION AND UMENT OF RPORATION RYCED.				