





NOTES:
1. CABLES 36" AND UNDER HAVE 1 LABEL CENTERED.
CABLES OVER 36" HAVE 2 LABELS, ONE AT EACH END
6.0" FROM THE FRONT OF THE CONNECTOR.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT
ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.
UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



III III III

A			XX X X X X X X X X X X X X X X X X X X					C
3	CAGE CODE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	X=±.2 [5.08] FRACTIONS XX=±.02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1°			0	TOLERANCES:	I 50 CITE
3FKR5						ANCES:		DIMENSIONS
VTHANGARAJ	DRAWN BY		120 [3048] < L < 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0		CABLE LENGTH (L) TOLERANCES:		DIMENSIONS IN [] ARE MILLIMETERS
FMCA3125	ITEM NO.		L \(\le 300 \left[7620 \right] = +6 \left[152 \right] \end{4-0} \\ 300 \left[7620 \right] \(\text{L} = +5\% \text{L} \end{4-0} \)	L ≤ 12 [305] = +1 [25] / -0				
13125		SCALE N	SHEET 1 C	FAIRVIEW MICROWAVE CORPORATION ALL RIGHTS RESERVED.	THE INFORMATION AND	THE INCOMMATION AND		
Þ	REV	N/A	1	CORPORATION. SERVED.	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF	ON AND	4	