







NOTES:

- .> :→ FEMALE CONTACT ACCEPTS PIN SIZE ϕ .015 [0.38] \mathbbmss{T} .100 [2.55] MAX. SEPARATE METAL CONTACT RING (PASSIVATED).

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



III III III

SIZE CAGE CODE D	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
DRAWN BY				CABLE LENGTH (L) TOLERANCES	
ITEM NO. FMCN 1612			L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 [1524] < L ≤ 120 [3048] = +4 [102] / -0	L) TOLERANCES:	ONS ARE INCHES
V1612 REV	SCALE N/A	SHEET OF 1	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION. ALL RIGHTS RESERVED.	THE INFORMATION AND	THIRD-ANGLE PROJECTION