











.079 [2.00] STRIPPING DIMENSIONS

- NOTES:

 1. CABLE ATTACHMENT:

 OUTER: SOLDER.

 INNER: SOLDER.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



an INFINIT® brand



≻	SIZE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	X=±2 [5.08] FRACTIONS XX=±.02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1°		TOLERANCES:	UNLESS OTHER
3F	CAGE CODE					
3FKR5						WISE SPEC
	DR.	WOH	-			SFIED
K.DANG	DRAWN BY	I ARE FOR REFERE	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = 4 [102] / -0 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0		CABLE LENGTH	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
FMCN1727	ITEM NO.	NCE ONLY.			CABLE LENGTH (L) TOLERANCES:	ONS ARE INCHES
		SCALE	SHEET	FAIRVIE		_
			_	THIRD-ANGLE PROJECTION THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF IEW MICROWANE CORPORA ALL RIGHTS RESERVED.		
	Z)	N/A	유	IS DOC OPERT AVE CO RESE	ATIO! /	. TA
⊳	REV		_	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION. ALL RIGHTS RESERVED.	AND	