


- Female Contact accepts PIN Size \emptyset .015 [0.38] \mathbbmss{T} .071 [1.80] Max. Separate metal Contact RING (passivated).

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.





TITLE

Þ	SIZE		X=±.2 [5.08] FRACTIONS XX=±.02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1°					UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS	
<u>ω</u>	CAGE CODE	ALL DIMENSIONS SHO				TOLER	1		
3FKR5	ĎE					TOLERANCES:			
MVEERAPPAN	DRAWN BY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY	_	12 [305] < L ≤ 60 60 [1524] < L ≤ 120		CABLE LENGTH (L) TOLERANCES:	יייין [] איר אווירבוואור ויבויכי	HED LEADING DIMENSIC	
FMCN1774	ITEM NO.	NCE ONLY.	L ≤ 12 [305] = +1 [25] / 0 12 [305] < L ≤ 60 [1824] = +2 [51] / 0 60 [1824] < L ≤ 120 [3048] = +4 [102] / 0 120 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0			L) TOLERANCES:		ONS ARE INCHES	
		SCALE N	SHEET 1 C						
≻	REV	N/A)F 1	CORPORATION. SERVED.	OJECTION				