





NOTES:
1. FEMALE CONTACT ACCEPTS PIN SIZE Ø.012 [0.30] ▼.071 [1.80] MAX.
2. SEPARATE METAL CONTACT RING (PASSIVATED).

MOUNTING HOLES PATTERN

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



TIT IE

an INFINIT® brand

						\Ve [™]
>	SIZE		X=±.2 [5.08] FRACTIONS XX=±.02 [.51] ±1/32 XXX=±.005[.13] ANGLES±1°			
3FKR5	CAGE CODE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY			TOLERANCES:	LESS OTHERWISE SPEC
MVEERAPPAN	DRAWN BY		_		CABLE LENGTH (L) TOLERANCES	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS DIMENSIONS IN [] ARE MILLIMETERS
FMCN1780	ITEM NO.	NCE ONLY.	120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 SHEET 300 [7620] < L = +5%L / -0	L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0	(L) TOLERANCES:	ONS ARE INCHES
11780	REV	SCALE N/A	SHEET 1 OF	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATIO ALL RIGHTS RESERVED.	THE INFORMATION AND	THIRD-ANGLE PROJECTION
Þ	ΞV	-	1	OMENT OF RPORATION. RVED.	AND	