

STRIPPING DIMENSIONS


NOTES:

1. CABLE ATTACHMENT:
OUTER: CRIMP.
INNTER: SOLDER/CRIMP.

2. CRIMP SIZE REQUIRED:
CONTACT: .36" [0.92] SQ CRIMP TOOL.
RERRULE: .216" [5.5] HEX CRIMP TOOL.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES



an INFINIT® brand

TITLE

⊳	SIZE	ALL DIM	$X = \pm .2$ [5.08] $XX = \pm .02$ [.51] $XXX = \pm .005$ [.13]				Ç.	
ω	CAGE CODE					TOLERANCES:		
3FKR5	Œ	ENSIONS SHO	(± 1/32	ERACTIONS	NCES:	DIMENSIONS	
K.GLEBOVA	DRAWN BY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.				CABLE LENGTH (L) TOLERANCES	DIMENSIONS IN [] ARE MILLIMETERS	
FMCN1816	ITEM NO.	NCE ONLY.	L \(\) 300 [7620] \(\) +6 [152] / -0 300 [7620] \(\) L \(\) +5%L / -0	12 [305] < L ≤ 60 [1524] = +2 [51] / -0 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0	L ≤ 12 [305] = +1 [25] / -0	L) TOLERANCES:		
1816		SCALE N	SHEET 1 C	THE INFORMA ESIGN IN THIS IS THE PROP W MICROWAV ALL RIGHTS F				
⊳	REV	N/A	OF 1	CORPORATION.	DOCUMENT RTY OF	ION AND	4	