









## NOTES:

[6.6]

.26

ΤYΡ

3X K TYPE FEMALE CONNECTOR

.31 [7.9]

11.2

[22.4]

.88

LABEL PER ILS-100-02. FOR INTERNAL REFERENCE ONLY. LABEL LOCATION FOR REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



an INFINIT® brand

TIT IE

≻	SIZE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	XX = ± ± X = ±				UNLE
<del>Ω</del>	CAGE CODE		X=±.2 [5.08] FRACTIONS  XX=±.02 [.51] ±102  XXX=±.005[.13] ANGLES±1° 12 [3048] < L≤300  XXX=±.005[.13] ANGLES±1° 120 [3048] < L≤300  300 [76]		7 [5 08]	TOLERANCES:	SS OTHER
3FKR5					NCES:	WISE SPECIF	
KGLEBOVA	DRAWN BY				_	CABLE LENGTH (L) TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
FMSW6480	ITEM NO.	NCE ONLY.	12 [305] < L ≤ 60 [1824] = +2 [51] / 0 60 [1524] < L ≤ 120 [3048] = +4 [102] / 0 120 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / -0			(L) TOLERANCES:	ONS ARE INCHES
		SCALE N	SHEET 1 C	THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION ALL RIGHTS RESERVED.  SHEET OF			THIRD-ANGLE PROJECTION
≻	REV	N/A	)F 2	CORPORATION. SERVED.	DOCUMENT RTY OF	ON AND	OVECTION