





## .46 [11.7] ΤYΡ [22.4].88 2.75 [69.9] • .88 [22.4] U CONNECTOR 3X N FEMALE

## NOTES:

LABEL LOCATION FOR REFERENCE ONLY. LABEL PER ILS-100-02. FOR INTERNAL REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

CABLE LENGTH (L) TOLERANCES:





				an INFINITE brand	
	A		X=±.2 [5.08] FRACTIONS XX=±.02 [.51] ±1.032 XXX=±.005[.13] ANGLES±1°		
	3FKR5	ALL DIME			
	3FKR5	ENSIONS SHO	FRACTIONS ± 1/32 ANGLES ± 1°		
	KGLEBOVA ITEM NO.	OWN ARE FC	12 [305] 60 [1524] < 120 [3048] <		
	BOVA	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.			
	FMSW6491 REV A	CE ONLY.	L ≤ 12 [305] = +1 [25] / 0 <l -0<br="" 60="" [1524]="+2" [51]="" ≤="">:L ≤ 120 [3048] = +4 [102] / -0 :L ≤ 300 [7620] = +6 [152] / -0 300 [7620] &lt; L = +5%L / -0</l>		
		SCALE	SHEET	FAIRVIEW MIC	DESIGN IN THIS DOCUMENT
		N/A	<b>1</b> OF	IEW MICROWAVE CORPOR	IN THIS DO
		<i>y</i>	2	ORPORATION. :RVED.	YOF