

.50 [12.6]

[63.5]

2.50

.70 [17.8] MAX

.37 [9.4]

.88 [22.4]

[22.4]


1.95 [49.5]

S/N: XXXXXXXXXX

 $^{-}$ 2X ϕ .152 [3.86] \mp THRU HOLES

A · -C
C · 1
B · 2
Vsw

ភ



NOTES:

.46 [11.7] TYP

2.75 [69.9]

3X N FEMALE CONNECTOR

.92

. LABEL PER ILS-100-02. FOR INTERNAL REFERENCE ONLY. LABEL LOCATION FOR REFERENCE ONLY.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.



an INFINIT® brand

TIT IE

≻	SIZE		3000		UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS	
3F	CAGE CODE	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	$ \begin{array}{llllllllllllllllllllllllllllllllllll$			TOLERANCES
3FKR5						NCES:
KGLEBOVA	DRAWN BY					CABLE LENGTH (L) TOLERANCES
FMSW6493	ITEM NO.	NCE ONLY.				(L) TOLERANCES:
		SCALE N/A	SHEET 1	DESIGN IN THIS DOCUMENT IS THE PROPERTY OF FAIRVIEW MICROWAVE CORPORATION ALL RIGHTS RESERVED.	THE INFORMATION AND	THIRD-ANGLE PROJECTION
⊳	REV		of 2	RTY OF CORPORATION. SERVED.	ION AND	OFECTION