



STANDARD TOLERANCES
.X ±0.2
.XX ±0.01
.XXX ±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTE:

HEAT SINK REQUIRED FOR PROPER OPERATION, UNIT IS COOLED BY CONDUCTING TO HEAT SINK.

15	14	13	12	1	10	9	∞	7	6	5	4	ω	2	_	PIN
OVER-TEMP BIT	N/C	N/C	GND	GND	+28V	+28V	BLANKING TTL	OVER-CURRENT BIT	N/C	N/C	GND	GND	+28V	+28V	DESCRIPTION

77
╬┺
77
~ 0.1
ö L .
<u></u>
×
\circ
NEN O
45
\Box
- N
4
-15
STI
02
\sim
~
z<
T
Z \ 4
D.J
7
40
Crov EMAND.
_ <
_
\sim \sim
ν
7
7
₹ ₹₽
1-

TITLE

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE	DWG NO
06/27/18	SPA-0
SHEET	SPA-030-50-50-SMA
1 OF 1	-SMA
SCALE	
N/A	CAGE CODE
SIZE A	
7361	3FKR5