



STANDARD TOLERANCES
.X ±0.2
.XX ±0.01
.XXX ±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTE:

HEAT SINK REQUIRED FOR PROPER OPERATION, UNIT IS COOLED BY CONDUCTING TO HEAT SINK.

15	14	13	12	=	10	9	œ	7	တ	Ŋ	4	ω	2	_	PN
OVER-TEMP BIT	N/C	N/C	GND	GND	+28V	+28V	BLANKING TTL	OVER-CURRENT BIT	N/C	N/C	GND	GND	+28V	+28V	DESCRIPTION

RFC
ZOMI
Vie
WIS
EMA T
N N N
Za/
70 10
D version of

TITLE

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

CAD FILE	DWG NO
06/27/18	SPA-C
SHEET	SPA-060-60-10-SMA
1 OF 1)-SMA
SCALE N/A	CA
	CAGE CODE
SIZE A	
7361	3FKR5