







RECOMMENDED STRIPPING DIMENSION

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS, DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

MICTOWAVE

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS



TITLE

A Size		.XXX = ±.005[.13]	× × = = = = = = = = = = = = = = = = = =		UNLE
CAGE CODE 3FKR5	ALL DIMENSIONS SHC	X = ±.2 [5.08] FRACTIONS XX = ±.02 [.51] ± 1/32 XX = ±.005[.13] ANGLES ± 1°		TOLERANCES:	SS OTHER
					RWISE SPECIFI
DRAWN BY DMAY	ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.	120 [3048] < L ≤ 300 [7620] = +6 [152] / -0 300 [7620] < L = +5%L / -0	L ≤ 12 12 [305] < L ≤ 60 60 [4524] < 1 < 120	CABLE LENGTH (L) TOLERANCES:	UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS
TC-400	NCE ONLY.	L ≤ 12 [305] = +1 [25] / 0 12 [305] < L ≤ 60 [1824] = +2 [51] / 0 60 [1524] < L ≤ 120 [3048] = 4 [102] / 0 120 [3048] < L ≤ 300 [7620] = +6 [152] / 0 300 [7620] < L = +5%L / 0		L) TOLERANCES:	ONS ARE INCHES
TC-400-NF-X	SCALE N	THE INFORMATION AND DESIGNA IN THIS DOCUMENT IS THE PROPERTY OF FAIRWEIM MICROWAVE CORPORATION ALL RIGHTS RESERVED. SHEET 1 OF 1			
A REV	N/A	OF 1	NOCUMENT RTY OF CORPORATION.	ION AND	OJECTION