

# TNC Male (Plug) to Female (Jack) Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz



# **FMAD91788**

## Configuration

- TNC Plug Connector 1
- TNC Jack Connector 2

#### **Features**

- VSWR of 1.2:1 max up to 18 GHz
- **Applications**
- · General Purpose Test

- 50 Ohms Impedance
- · Radius Right Angle Body Geometry
- · Gold Plated Beryllium Copper Contact

## Description

The type TNC radius right angle adapter FMAD91788 from Fairview Microwave is part of a very large in-stock collection of RF interconnect components. Our type TNC to type TNC RF adapter comes with a 50 Ohm impedance. This adapter is manufactured to precise RF component specifications and has a maximum VSWR of 1.2:1. Our RF adapter has a dielectric withstanding voltage of 1000 Vrms.

This type TNC to type TNC adapter is constructed with the plug gender on side 1 and the jack gender on side 2. The type TNC plug to type TNC jack coaxial adapter from Fairview Microwave has a radius right angle body style. This radius right angle type TNC adapter is a 90 degree swept elbow adapter. Our RF adapter can be utilized to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. The FMAD91788 adapter has a length of 1.35 inches, a width of 0.56 inches, and a weight of 0.053 lbs.

Our in-series radius right angle RF adapter operates at a maximum frequency of 18 GHz. This type TNC plug to type TNC jack radio frequency adapter has a passivated stainless steel connector body. The Fairview Microwave FMAD91788 coaxial RF adapter operates at temperatures ranging from -65 to 165 degrees C. Additional dimensions and specifications for this adapter are on our downloadable PDF datasheet above.

Fairview Microwave's type TNC plug to type TNC jack radius right angle adapter is part of over one million RF microwave and millimeter wave components in stock for worldwide shipment. We also stock and custom-build type TNC coaxial cables that ship quickly from our facility for all your RF adapter component needs. Make your online purchase right now to take advantage of our same-business-day shipping. For further information on similar products, our expert technical support and trained sales team can get you the ideal 18 GHz radio frequency adapter as per your requirements.

## **Electrical Specifications**

| Description                          | Minimum | Typical | Maximum | Units |
|--------------------------------------|---------|---------|---------|-------|
| Frequency Range                      | DC      |         | 18      | GHz   |
| Impedance                            |         | 50      |         | Ohms  |
| VSWR                                 |         |         | 1.2:1   |       |
| Operating Voltage (AC)               |         |         | 500     | Vrms  |
| Dielectric Withstanding Voltage (AC) |         |         | 1,000   | Vrms  |
| Inner Conductor DC Resistance        |         |         | 6       | mOhms |
| Outer Conductor DC Resistance        |         |         | 2       | mOhms |
| Insulation Resistance                | 5,000   |         |         | MOhms |

# **Mechanical Specifications**

Size

Length 1.35 in [34.37 mm]



# TNC Male (Plug) to Female (Jack) Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz



## **FMAD91788**

| Width  | 0.56 in [14.22 mm] |
|--------|--------------------|
| Height | 1.34 in [33.99 mm] |
| Weight | 0.05 lbs [24.13 g] |

| Description                          | Connector 1                     | Connector 2                     |  |
|--------------------------------------|---------------------------------|---------------------------------|--|
| Polarity                             | Standard                        | Standard                        |  |
| Mating Cycles, Min                   | 500                             | 500                             |  |
| Mating Torque                        | 10 to 12 in-lbs 1.13 to 1.36 Nm | 10 to 12 in-lbs 1.13 to 1.36 Nm |  |
| Contact Captivation Axial Force, Min | 6 lbs [2.72 kg]                 | 6 lbs [2.72 kg]                 |  |
| Coupling Retention, Min              | 100 lbs [45.36 kg]              | 100 lbs [45.36 kg]              |  |

## **Material Specifications**

|              | Connector 1                |         | Connector 2                |         |
|--------------|----------------------------|---------|----------------------------|---------|
| Description  | Material                   | Plating | Material                   | Plating |
| Туре         | TNC Plug                   |         | TNC Jack                   |         |
| Contact      | Beryllium Copper           | Gold    | Beryllium Copper           | Gold    |
| Insulation   | PTFE                       |         | PTFE                       |         |
| Body         | Passivated Stainless Steel |         | Passivated Stainless Steel |         |
| Coupling Nut | Passivated Stainless Steel |         | Passivated Stainless Steel |         |

### **Environmental Specifications**

**Temperature** 

Operating Range -65 to +165 °C

Compliance Certifications (see product page for current document)

## **Plotted and Other Data**

TNC Male (Plug) to Female (Jack) Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: TNC Male (Plug) to Female (Jack) Radius Right Angle Adapter, VSWR 1.2 Max. DC-18GHz FMAD91788

URL: https://www.fairviewmicrowave.com/radius-ra-tnc-plug-to-tnc-jack-adapter-with-passivated-stainless-steel-body-fmad91788-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

