

4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA

FMAM3309



Features

- 1 MHz to 3 GHz Frequency Range
- P1dB: +20 dBm
- Small Signal Gain: 16 dB
- Gain Flatness: ± 1.5 dB
- 50 Ohm Input and Output Matched
- Output IP3: +35 dBm
- Advanced InGaP GaAs HBT Design
- -40 to +85°C Operating Temperature
- +15V / 110mA DC Positive Supply
- SMA Female Connectors
- Designed to meet MIL-STD-202 Test Conditions

Applications

- Laboratory Applications
- R&D Labs
- Test Instrumentation
- Military & Space
- Communication Systems
- Satellite Communications
- Wireless Communications
- Unmanned Systems
- Microwave Radio Systems
- Low Noise Amplifier
- General Purpose Amplification
- RF Front Ends

Description

The FMAM3309 is a broadband coaxial power amplifier, operating in the 1 MHz to 3 GHz frequency range. Impressive broadband typical performance includes 4 dB noise figure, 16 dB small signal gain, +20 dBm P1dB, and an output 3rd order intercept point of +35 dBm. This exceptional technical performance is achieved through the use of hybrid MIC design and advanced InGaP GaAs HBT devices. The low noise amplifier requires a +15V DC power supply, and operates over a temperature range of -40°C to +85°C. The rugged and compact package supports SMA Female connectors and RFI and Ground pins. And for highly reliable operation, the model is guaranteed to meet MIL-STD-202 environmental test conditions for Humidity, Shock, Vibration, and Altitude.

Electrical Specifications (TA= 25°C, VDC = 15 Vdc)

Description	Min	Typ	Max	Unit
Frequency Range	0.001		3	GHz
Gain	16	21		dB
Gain Flatness		± 1.5	± 2	dB
P1dB f = 1500 MHz	+20	+22		dBm
IP3	+33	+35		dBm
Reverse Isolation	-20	-23		dB
Noise Figure		4	4.5	dB
Input VSWR f = 1500 MHz		1.5:1	2:1	
Output VSWR f = 1500 MHz		2:1	2.5:1	
Operating DC Voltage	14	15	16	Vdc
Operating DC Current		110	130	mA
Operating DC Current at P1dB		22		mA
Operating Temperature Range (OTR)	0		+50	°C

4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier
with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA

FMAM3309



Mechanical Specifications

Size

Length	8.3 in [210.82 mm]
Width	3.4 in [86.36 mm]
Height	1.35 in [34.29 mm]
Weight	0.0901 lbs [40.87 g]
Input Connector	SMA Female
Output Connector	SMA Female

Environmental Specifications

Temperature

Operating Range	0 to +50 deg C
Storage Range	-40 to +100 deg C
Humidity	MIL-STD-202F, Method 103B, Condition B
Shock	MIL-STD-202F, Method 213B, Condition B
Vibration	MIL-STD-202F, Method 204D, Condition B
Altitude	MIL-STD-202F, Method 105C, Condition B

Compliance Certifications (see [product page](#) for current document)

CE Certification

Plotted and Other Data

Notes:


4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier
with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA



FMAM3309

Functional Block Diagram


Typical Performance Data Parameter, Typ Performance



4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier
with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA




FMAM3309



4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier
with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA



FMAM3309



4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier
with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA



FMAM3309

4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.



For additional information on this product, please click the following link: [4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA FMAM3309](https://www.fairviewmicrowave.com/1-mhz-3-ghz-low-noise-broadband-amplifier-fmam3309-p.aspx)

URL: <https://www.fairviewmicrowave.com/1-mhz-3-ghz-low-noise-broadband-amplifier-fmam3309-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMAM3309 CAD Drawing

4 dB NF, 1 MHz to 3 GHz, Low Noise Broadband Amplifier with 22 dBm, 21 dB Gain, 35 dBm IP3 and SMA



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.01
.XXX	±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

<div><div><div></div><div></div><div></div><div></div></div><div><div><div></div><div></div><div></div><div></div></div></div><div>Fairview Microwave</div><div>RF COMPONENTS ON DEMAND. <i>Done!</i></div></div>		<div>NOTES:</div> <div>1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.</div> <div>2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.</div> <div>3. DIMENSIONS ARE IN INCHES [mm].</div>								
TITLE		DWG NO				CAGE CODE				
		FMAM3309				3FKR5				
		CAD FILE	04/23/18	SHEET	1 OF 1	SCALE	N/A	SIZE	A	7361