

High Power GaAs Amplifier at 4 Watt Psat Operating from 8 GHz to 11 GHz with SMA

FMAM4015 is a broadband 4 W GaAs PHEMT MMIC-based coaxial power amplifier module designed to be used in a wide range of commercial and defense applications in the 8 to 11 GHz frequency range. The amplifier offers 28 dB small signal gain with ± 3 dB gain flatness. This performance is achieved through the use of advanced GaAs PHEMT MMIC circuitry. The amplifier requires manual voltage sequencing (see pages 4 & 5) and operates over the temperature range of -40°C to 85°C . This Innovative design is characterized by light weight (45 g) and small size (1.5"x1.2"x0.56"). An available finned heatsink (model FMAMC5014) is recommended to maintain an optimum baseplate temperature during operation.

Electrical Specifications

(TA = $+25^{\circ}\text{C}$, Vds = +5V, Idsq = 2.0 A, Vgg = -2.6V**)

Description	Min	Typ	Max	Unit
Frequency Range	8		11	GHz
Small Signal Gain	24	28		dB
Gain Flatness		± 3		dB
Pout at Sat.		+36		dBm
Efficiency Psat		25		%
Output Power at 1 dB Compression Point		+32		dBm
Impedance (Input)		50		Ohms
Impedance (Output)		50		Ohms
Input Return Loss		10		dB
Output Return Loss		6		dB
Operating DC Drain Source Voltage		5	6	Volts
Operating DC Gate Source Voltage		-2.6	-3	Volts
Operating Temperature Range	-40		+85	$^{\circ}\text{C}$
Thermal Resistance		2.3		$^{\circ}\text{C}/\text{W}$

Absolute Maximum Rating

Parameter	Rating	Units
Drain Source Voltage, Vds 1,2,3	+6	Volts
Gate Source Voltage Vdd	-3	Volts
Drain Source Current Idsq 1	0.2	A
Drain Source Current Idsq 2	0.9	A
Drain Source Current Idsq 3	2	A
Continuous Dissipation at 25°C	20	W
Channel Temperature	175	$^{\circ}\text{C}$
Operating Temperature (base-plate)	-40 to +85	$^{\circ}\text{C}$
Storage Temperature	-55 to +135	$^{\circ}\text{C}$



ESD Sensitive Material, Transport material in Approved
ESD bags. Handle only in approved
ESD Workstation.



Features:

- 8 GHz to 11 GHz Frequency Range
- P1dB Output Power: 32 dBm typ
- Psat: 36 dBm typ
- Small Signal Gain: 28 dB typ
- Gain Flatness: ± 3 dB typ
- Power Added Efficiency @Psat: 25%
- Noise Figure: 10 dB
- 50 Ohm Input and Output Matched
- -40 to $+85^{\circ}\text{C}$ Operating Temperature
- Unconditionally Stable
- Small Size & Light Weight
- EAR99 (No Export License Required)
- Manual Voltage Sequencing
- Optional Heatsink Available: Model FMAMC5014

Applications:

- Telecom Infrastructure
- Fixed Microwave Backhaul
- Microwave Radio Systems
- Military & Space
- Radar & Sensors
- Satellite Communication
- Commercial Avionics
- Driver Amplifier
- High Power Output
- General Purpose Amplification

Fairview Microwave
 301 Leora Ln., Suite 100
 Lewisville, TX 75056
 Tel: 1-800-715-4396 / (972) 649-6678
 Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Mechanical Specifications

Size	
Length	1.2 in [30.48 mm]
Width	1.5 in [38.1 mm]
Height	0.56 in [14.22 mm]
Weight	0.112 lbs [50.8 g]
Input Connector	SMA Female
Output Connector	SMA Female

Environmental Specifications

Temperature	
Operating Range	-40 to +85 deg C
Storage Range	-55 to +135 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

- Notes:
- Values at 25 °C, sea level
 - ESD Sensitive Material, Transport material in Approved ESD bags. Handle only in approved ESD Workstation.
 - Heat Sink Required for Proper Operation, Unit is cooled by conduction to heat sink.

Amplifier Power-up Precautions

- 1.) Confirm that proper ESD precautions and controls are always in place before handling any Amplifier module.
- 2.) Confirm adequate thermal management is in place to effectively dissipate heat away from the Amplifier package. The Amplifier operational baseplate temperature must be within the operational temperature range stated in the Amplifier datasheet. Depending on the design and thermal requirements, using a heatsink with cooling fan is always recommended for safe reliable operation. A heat sink without a cooling fan may also be used. Damage caused from overheating will void the warranty.
- 3.) Confirm adequate system grounding is established. The DC power supply and Amplifier must have a common ground in order to operate properly.
- 4.) Power Amplifiers may require additional DC Current when initially powered-up. Depending on the design, the input current draw could range from an additional 10% to 100% above the maximum rated DC current of the Amplifier. This varies based on product part number.
- 5.) Confirm the DC power supply, if limited, is set to allow for additional start-up current that's rated for the Power Amplifier.
- 6.) Confirm the system is designed and calibrated for 50 ohms. Any impedance mismatch may cause performance issues.
- 7.) Perform a CALIBRATION (if required) with the loads before connecting the Amplifier to the Network Analyzer to ensure proper performance.
- 8.) Use a fixed attenuator between the signal source and input port of the Amplifier to optimize the input VSWR match.
- 9.) Confirm the input power level at the input port of the amplifier does not exceed the maximum rated limit for input power (as stated in the Amplifier datasheet).
 P_{in} for Small Signal Gain = P1dB-SSG-10 dB
 P_{in} for P1dB = P1dB-SSG+1 dB
- 10.) Confirm the Network Analyzer is always connected to the Amplifier first before DC power is applied to the Amplifier.
- 11.) As long as the input and output ports of the amplifier are connected to a 50Ohm load and RF signal power is applied, the Amplifier can be powered up with DC voltage.
- 12.) Confirm the Amplifier output load is matched for a 50 Ohm impedance and will not exceed the maximum rated VSWR or Return Loss limit for the Amplifier. Exceeding the maximum rated VSWR or Return Loss limit will result in reflected signal power that could damage the Amplifier and void the warranty.
- 13.) **Power Amplifier connected to an Antenna for signal transmission** - It's strongly recommended to use a high power fixed attenuator pad or an Isolator between the output port of the Amplifier and input port to the antenna. Any reflected signal power due to impedance mismatch will likely damage the Amplifier and void the warranty.
- 14.) The attenuator or isolator used at the output port of the Amplifier must be rated to handle the output power level and operational frequency band of the amplifier.

GaAs PHEMT MMIC-Based Power up sequence

1. Connect common ports
 - a. Connect single GND lead
 - b. Connect all -V_{gg} ports together**
 - c. Connect all +V_{ds} ports together
2. Connect the load, attenuator to protect the VNA.
3. Connect the input port, may have an attenuator at the input (perform the CAL with the loads before connecting the amplifier to the VNA).
4. Apply the -V_{gg} voltage -2.6 V_{gg} (Always apply -V_{gg} first).
5. Apply the +V_{ds} +5 Volts (always apply +V_{ds} second).

**All 5 V_{ds} voltage pins (V_{ds1}, V_{ds2}, V_{ds3}) can be tied together using external wiring to a common voltage source (+5 V_{dc} typical). The gate voltage of -2.6 V_{gg} is applied only to the single V_{gg} voltage pin.







illustration of Amplifier mounted on Heatsink.
Heatsink model **FMAMC5014** sold separately.
(Picture shown for Reference Only)

Typical Performance Data



*Bias at: $V_{ds1,2,3} = +5V$, $V_{gg} = -2.6V$, $I_{dsq1} = 0.14A$, $I_{dsq2} = 0.56A$, $I_{dsq3} = 1.3A$.




*Bias is $V_{ds} = +5V$, $I_{dsq} = 2.0 A$, $V_{gg} = -2.6V$.

High Power GaAs Amplifier at 4 Watt Psat Operating from 8 GHz to 11 GHz with SMA from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [High Power GaAs Amplifier at 4 Watt Psat Operating from 8 GHz to 11 GHz with SMA FMAM4015](#)

URL: <https://www.fairviewmicrowave.com/high-power-amplifier-4watt-28db-fmam4015-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



T-Rev.D