

WiFi 6e, 2400-2500/4900-7250 MHz
4/7 dBi, Stick Omni, N Female

FMANOM1160



Features

- Type N Female Connector
- Outdoor Rated Omnidirectional Antenna
- 2.4 GHz, 5 GHz, 6 GHz WiFi Bands
- 4 dBi gain

Applications

- Infotainment systems, Routers, WiFi hotspots, HD video transmission, Gateways, Dash cameras, Public transportation
- WiFi 6e (802.11ax) networks
- Connected cars or self-driving cars, Fleet management, Logistics
- Public Safety Networks
- IoT, Industrial IoT, Zigbee, Bluetooth, WiFi

Description

The FMANOM1160 WiFi 6e Stick Omni Antenna from Fairview Microwave is a high performance omnidirectional antenna designed for the 2400 MHz to 7125 MHz bands and is available to ship same day. It features a Type N Female connector, UV protection, omni-directional patterns for outdoor or indoor use. The FMANOM1160 is ideally suited for 802.11 protocols including 802.11ax as well as IoT, Zigbee and Bluetooth.

The Fairview Microwave high performance omni FMANOM1160 is a rugged antenna providing broad coverage, low latency, increased network capacity and 4 dBi gain. This N Type Female omnidirectional antenna is suitable for commercial radios and access points in public and private networks that are equipped with N Male connectors. Fairview Microwave's FMANOM1160 supports 2.4, 5 and 6 GHz bands.

This WiFi 6e FMANOM1160 omni antenna N Type Female connectors, as well as our wide selection of superior quality RF parts, ships same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on antennas or other Fairview Microwave products.

Configuration

Design	Omni
Band Type	Dual
Radiation Pattern	Omnidirectional
Polarization	Vertical
Connector Type	N Female
Number of Ports	1

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	2,400		7,250	MHz
Input VSWR			2:1	
Impedance		50		Ohms
Input Power			50	Watts

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Frequency	2.4 to 2.5	4.9 to 7.25				GHz
Gain	4	7				dBi
Horizontal HPBW	360	360				Degrees
Vertical HPBW	30	18				Degrees

WiFi 6e, 2400-2500/4900-7250 MHz
4/7 dBi, Stick Omni, N Female

FMANOM1160



Mechanical Specifications

Radome Material	Fiberglass
Size	
Length	0 in [0 mm]
Width	0 in [0 mm]
Height	0 in [0 mm]
Weight	0.85 lbs [385.55 g]

Environmental Specifications

Temperature	
Operating Range	-40 to +70 deg C
Wind Survivability	124 MPH [199.56 KPH]
Humidity	5 to 95 %


Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Radiation Pattern

Radiation Patterns at 2450 MHz





WiFi 6e, 2400-2500/4900-7250 MHz
4/7 dBi, Stick Omni, N Female

FMANOM1160



Radiation Patterns of 5850 MHz





WiFi 6e, 2400-2500/4900-7250 MHz
4/7 dBi, Stick Omni, N Female

FMANOM1160



Radiation Patterns of 7125 MHz



WiFi 6e, 2400-2500/4900-7250 MHz
4/7 dBi, Stick Omni, N Female

FMANOM1160



Appendix

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

WiFi 6e, 2400-2500/4900-7250 MHz 4/7 dBi, Stick Omni, N Female from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [WiFi 6e, 2400-2500/4900-7250 MHz 4/7 dBi, Stick Omni, N Female FMANOM1160](https://www.fairviewmicrowave.com/product/antennas/dbi-dualband-omni-antenna-2400-7250-mhz-n-type-connector-fmanom1160)

URL: <https://www.fairviewmicrowave.com/product/antennas/dbi-dualband-omni-antenna-2400-7250-mhz-n-type-connector-fmanom1160.html>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMANOM1160 CAD Drawing

WiFi 6e, 2400-2500/4900-7250 MHz 4/7 dBi, Stick Omni, N Female

