

## Low Loss RA TNC Male to MCX Plug Cable RG174 Coax in 12 Inch

The RA TNC male to MCX plug 12 inch cable using RG174 coax, part number FMC00250-12, from Fairview Microwave is in-stock and ships same day. This Fairview TNC to MCX cable assembly has a male to plug gender configuration with 50 ohm flexible RG174 coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. The FMC00250-12 TNC male to MCX plug cable assembly operates to 1 GHz. The right angle TNC interface on the RG174 cable allows for easier connections in tight spaces.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

### Electrical Specifications

| Description             | Min   | Typ      | Max   | Units        |
|-------------------------|-------|----------|-------|--------------|
| Frequency Range         | DC    |          | 1,000 | MHz          |
| Velocity of Propagation |       | 66       |       | %            |
| Capacitance             | 31.08 | [101.97] |       | pF/ft [pF/m] |

### Performance by Frequency

| Description           | F1   | F2   | F3   | F4   | F5    | Units |
|-----------------------|------|------|------|------|-------|-------|
| Frequency             | 50   | 100  | 250  | 500  | 1,000 | MHz   |
| Insertion Loss (Typ.) | 0.34 | 0.38 | 0.43 | 0.51 | 0.62  | dB    |

#### Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax cable and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.1 dB for the straight connector and 0.2 dB for the right angle connector.

### Mechanical Specifications

#### Cable Assembly

|          |                    |
|----------|--------------------|
| Length*  | 12 in [304.8 mm]   |
| Diameter | 0.57 in [14.48 mm] |

#### Cable

|                                      |                     |
|--------------------------------------|---------------------|
| Cable Type                           | RG174               |
| Impedance                            | 50 Ohms             |
| Inner Conductor Type                 | Stranded            |
| Inner Conductor Material and Plating | Copper Clad Steel   |
| Dielectric Type                      | PE                  |
| Number of Shields                    | 1                   |
| Shield Layer 1                       | Tinned Copper Braid |
| Jacket Material                      | PVC, Black          |
| Jacket Diameter                      | 0.11 in [2.79 mm]   |



### Configuration:

- TNC Male Right Angle
- MCX Plug
- RG174

### Features:

- Max Frequency 1 GHz
- 66% Phase Velocity
- PVC Jacket

### Applications:

- General Purpose
- Laboratory Use

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

## Connectors

| Description                     | Connector 1   | Connector 2    |
|---------------------------------|---------------|----------------|
| Type                            | TNC Male      | MCX Plug       |
| Specification                   |               | CECC 22220     |
| Impedance                       | 50 Ohms       | 50 Ohms        |
| Contact Material & Plating      | Brass, Gold   | Brass, Gold    |
| Contact Plating Spec.           |               | 30 µin minimum |
| Dielectric Type                 | Delrin        | PTFE           |
| Body Material & Plating         | Brass, Nickel | Brass, Gold    |
| Body Plating Spec.              |               | 3 µin minimum  |
| Coupling Nut Material & Plating | Brass, Nickel |                |

## Environmental Specifications

### Temperature

Operating Range -40 to +80 deg C

## Compliance Certifications (see [product page](#) for current document)

## Plotted and Other Data

Notes:

## How to Order

Part Number Configuration:

**FMC00250 - xx uu**

cm = Centimeters  
 <blank> = Inches

Length

Example: FMC00250-12 = 12 inches long cable  
 FMC00250-100cm = 100 cm long cable

Low Loss RA TNC Male to MCX Plug Cable RG174 Coax in 12 Inch from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: [Low Loss RA TNC Male to MCX Plug Cable RG174 Coax in 12 Inch FMC00250-12](#)

URL: <https://www.fairviewmicrowave.com/low-loss-ra-tnc-male-mcx-plug-cable-rg174-coax-fmc00250-12-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

