

1.85mm Male to 2.92mm Female Bulkhead Cable FM-SR086TBJ Coax

FMCA100348

Configuration

· Connector 1: 1.85mm Male

· Connector 2: 2.92mm Female Bulkhead

Cable Type: FM-SR086TBJCoax Flex Type: Formable

Features

- Shielding Effectivity > 100 dB
- · 69.5% Phase Velocity
- FEP Jacket

Applications

· General Purpose

· Laboratory Use

Description

The 1.85mm male to 2.92mm female bulkhead cable using FM-SR086TBJ coax, part number FMCA100348, from Fairview Microwave is in-stock and ships same day. This Fairview 1.85mm to 2.92mm cable assembly has a male to female gender configuration with 50 ohm formable FM-SR086TBJ coax. Fairview Microwave's formable RF cable assemblies provide an alternative to costly pre-formed semi-rigid assemblies since they are hand formable. Our RF cable assembly with 2.92mm bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Velocity of Propagation		69.5		%
RF Shielding	100			dB
Group Delay		1.43 [4.69]		ns/ft [ns/m]
Capacitance		29 [95.14]		pF/ft [pF/m]
DC Resistance Inner Conductor		65.7 [215.55]		Ohms/1000ft [Ohms/Km]
DC Resistance Outer Conductor		10.2 [33.46]		Ohms/1000ft [Ohms/Km]

Mechanical Specifications

Cable Assembly

 Width/Diameter
 0.5 in [12.7 mm]

 Weight
 0.05 lbs [22.68 g]

Cable

Cable Type FM-SR086TBJ



1.85mm Male to 2.92mm Female Bulkhead Cable FM-SR086TBJ Coax

FMCA100348

Impedance
Inner Conductor Type
Inner Conductor Material and Plating
Dielectric Type
Number of Shields
Outer Conductor 1 Material and Plating
Jacket Material
Jacket Diameter
One Time Minimum Bend Radius

Repeated Minimum Bend Radius

50 Ohms
Solid
Copper Clad Steel, Silver
PTFE
1
Tinned Copper Composite Braid
FEP, Black
0.105 in [2.67 mm]
0.5 in [12.7 mm]
0.787 in [19.99 mm]

Connectors

Description	Connector 1	Connector 2	
Туре	1.85mm Male	2.92mm Female Bulkhead	
Impedance	50 Ohms	50 Ohms	
Configuration	Straight	Straight	
Mating Cycles	500		
Contact Material and Plating	Beryllium Copper, Gold over Nickel	Beryllium Copper, Gold over Nickel	
Contact Plating Specification	50 μin minimum	50 µin minimum	
Dielectric Type	PEI		
Body Material and Plating	Beryllium Copper, Gold over Nickel	Passivated Stainless Steel	
Body Plating Specification	50 μin minimum	SAE-AMS-2700	
Coupling Nut Material and Plating	Passivated Stainless Steel		
Coupling Nut Plating Specification	ASTM-A582		
Hex Size	5/16 inch		
Torque	8 in-lbs 0.9 Nm		

Environmental Specifications

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:



1.85mm Male to 2.92mm Female Bulkhead Cable FM-SR086TBJ Coax



FMCA100348

Typical Performance Data

How to Order

Part Number Configuration:

FMCA100348 - xx uu

Unit of Measure:
cm = Centimeters

Length
Base Number

Example: FMCA100348-12 = 12 inches long cable FMCA100348-100cm = 100 cm long cable

1.85mm Male to 2.92mm Female Bulkhead Cable FM-SR086TBJ Coax from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: 1.85mm Male to 2.92mm Female Bulkhead Cable FM-SR086TBJ Coax FMCA100348

URL: https://www.fairviewmicrowave.com/1.85mm-male-to-2.92mm-female-bulkhead-cable-fm-sr086tbj-coax-fmca100348-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

