

## Low PIM 4.3-10 Female Bulkhead to N Male Cable TFT-402 Coax in 12 Inch Using Times Microwave Components

The 4.3-10 female bulkhead to type N male 12 inch cable using TFT-402 coax, part number FMCA2440-12, from Fairview Microwave is in-stock and ships same day. This Fairview 4.3-10 to type N cable assembly has a female to male gender configuration with 50 ohm flexible TFT-402 coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. Our low PIM design offers excellent passive intermodulation performance with PIM levels better than -160 dBc. The FMCA2440-12 4.3-10 female to type N male cable assembly operates to 5.8 GHz. Our RF cable assembly with 4.3-10 bulkhead interface allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The double shielding of this Fairview cable assembly provides excellent shielding effectiveness of better than -80 dB.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

### Electrical Specifications

| Description                   | Min | Typ         | Max   | Units                                         |
|-------------------------------|-----|-------------|-------|-----------------------------------------------|
| Frequency Range               | DC  |             | 5.8   | GHz                                           |
| VSWR                          |     |             | 1.4:1 |                                               |
| Velocity of Propagation       |     | 76          |       | %                                             |
| RF Shielding                  | -80 |             |       | dB                                            |
| Passive Intermodulation       |     |             | -160  | dBc                                           |
| Capacitance                   |     | 26.7 [87.6] |       | pF/ft [pF/m]                                  |
| DC Resistance Inner Conductor |     | 8.5 [27.89] |       | $\Omega/1000\text{ft}$ [ $\Omega/\text{Km}$ ] |
| DC Resistance Outer Conductor |     | 5.6 [18.37] |       | $\Omega/1000\text{ft}$ [ $\Omega/\text{Km}$ ] |

### Performance by Frequency

| Description           | F1   | F2   | F3   | F4   | F5   | Units |
|-----------------------|------|------|------|------|------|-------|
| Frequency             | 0.25 | 0.5  | 1    | 2.5  | 5.8  | GHz   |
| Insertion Loss (Typ.) | 0.16 | 0.22 | 0.31 | 0.49 | 0.75 | dB    |

#### Electrical Specification Notes:

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of  $0.1 \cdot \sqrt{\text{FGHz}}$  dB per connector.

### Mechanical Specifications

#### Cable Assembly

|          |                     |
|----------|---------------------|
| Length*  | 12 in [304.8 mm]    |
| Diameter | 0.867 in [22.02 mm] |



### Configuration:

- 4.3-10 Female Bulkhead
- N Male
- TFT-402

### Features:

- Max Frequency 5.8 GHz
- Low PIM: -160 dBc Max
- Shielding Effectivity > -80 dB
- 76% Phase Velocity
- Double Shielded
- FEP Jacket
- 500 Mating Cycles

### Applications:

- General Purpose
- Laboratory Use
- Low PIM Applications
- Indoor and Outdoor Use
- Plenum Rated Applications

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

**Cable**

|                                      |                            |
|--------------------------------------|----------------------------|
| Cable Type                           | TFT-402                    |
| Impedance                            | 50 Ohms                    |
| Inner Conductor Type                 | Solid                      |
| Inner Conductor Material and Plating | Copper, Silver             |
| Dielectric Type                      | PTFE                       |
| Number of Shields                    | 2                          |
| Shield Layer 1                       | Silver Plated Copper Braid |
| Shield Layer 2                       | Tinned Copper Braid        |
| Jacket Material                      | FEP, Blue                  |
| Jacket Diameter                      | 0.16 in [4.06 mm]          |

One Time Minimum Bend Radius 0.75 in [19.05 mm]

**Connectors**

| Description                     | Connector 1             | Connector 2      |
|---------------------------------|-------------------------|------------------|
| Type                            | 4.3-10 Female           | N Male           |
| Mount Method                    | Bulkhead                |                  |
| Impedance                       | 50 Ohms                 | 50 Ohms          |
| Mating Cycles                   | 500                     | 500              |
| Contact Material & Plating      | Phosphor Bronze, Silver | Brass, Silver    |
| Contact Plating Spec.           | 200 µin                 | 200 µin          |
| Dielectric Type                 | PTFE                    | PTFE             |
| Outer Cond Material & Plating   | Brass, Tri-Metal        |                  |
| Outer Cond Plating Spec.        | 80 µin                  |                  |
| Body Material & Plating         | Brass, Tri-Metal        | Brass, Tri-Metal |
| Body Plating Spec.              | 80 µin                  | 80 µin           |
| Coupling Nut Material & Plating |                         | Brass, Tri-Metal |
| Coupling Nut Plating Spec.      |                         | 80 µin           |
| Torque                          |                         | 15 in-lbs 1.7 Nm |

**Environmental Specifications**
**Temperature**

Operating Range -40 to +85 deg C

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

**How to Order**

Part Number Configuration:

**FMCA2440 - xx uu**

cm = Centimeters  
 <blank> = Inches  
 Length

Example: FMCA2440-12 = 12 inches long cable  
 FMCA2440-100cm = 100 cm long cable

Low PIM 4.3-10 Female Bulkhead to N Male Cable TFT-402 Coax in 12 Inch Using Times Microwave Components from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: [Low PIM 4.3-10 Female Bulkhead to N Male Cable TFT-402 Coax in 12 Inch Using Times Microwave Components FMCA2440-12](https://www.fairviewmicrowave.com/low-pim-4.3-10-female-n-male-cable-tft-402-coax-fmca2440-12-p.aspx)

URL: <https://www.fairviewmicrowave.com/low-pim-4.3-10-female-n-male-cable-tft-402-coax-fmca2440-12-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



