

2.92mm Male to 2.92mm Female Cable Tinned Copper RG402 Type .141 Coax in 200 CM Length

The 2.92mm male to 2.92mm female 200 cm cable using Tinned Copper RG402 type .141 coax, part number FMCA2918-200CM, from Fairview Microwave is in-stock and ships same day. This Fairview 2.92mm to 2.92mm cable assembly has a male to female gender configuration with 50 ohm semi-rigid FM-SR141CUTN-STR coax. Fairview Microwave's semi-rigid RF cable assemblies are ideal for high performance applications and can be formed, using proper tooling, to the routing pattern required.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.



Configuration:

- 2.92mm Male
- 2.92mm Female
- FM-SR141CUTN-STR

Applications:

- General Purpose
- Laboratory Use

Mechanical Specifications

Cable Assembly

| | |
|---------|----------------------|
| Length* | 78.74 in [200 cm] |
| Weight | 0.234 lbs [106.14 g] |

Cable

| | |
|--------------------------------------|---------------------------|
| Cable Type | FM-SR141CUTN-STR |
| Impedance | 50 Ohms |
| Inner Conductor Type | Solid |
| Inner Conductor Material and Plating | Copper Clad Steel, Silver |
| Dielectric Type | PTFE |
| Number of Shields | 1 |
| Shield Layer 1 | Tinned Copper |

| | |
|------------------------------|----------------|
| One Time Minimum Bend Radius | 1 in [25.4 mm] |
|------------------------------|----------------|

Connectors

| Description | Connector 1 | Connector 2 |
|---------------------------------|------------------------------------|----------------------------|
| Type | 2.92mm Male | 2.92mm Female |
| Impedance | 50 Ohms | 50 Ohms |
| Contact Material & Plating | Beryllium Copper, Gold over Nickel | Gold |
| Contact Plating Spec. | 50 µin minimum | |
| Dielectric Type | PCTFE | PPO |
| Body Material & Plating | Stainless Steel, Gold over Nickel | Passivated Stainless Steel |
| Body Plating Spec. | 50 µin minimum | |
| Coupling Nut Material & Plating | Stainless Steel, Gold over Nickel | |
| Coupling Nut Plating Spec. | 50 µin minimum | |
| Hex Size | 5/16 inch | |
| Torque | 8 in-lbs 0.9 Nm | |

Fairview Microwave
301 Leora Ln., Suite 100
Lewisville, TX 75056
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

How to Order

Part Number Configuration:

FMCA2918 - xx uu

cm = Centimeters
<blank> = Inches

Length

Example: FMCA2918-12 = 12 inches long cable
FMCA2918-100cm = 100 cm long cable

2.92mm Male to 2.92mm Female Cable Tinned Copper RG402 Type .141 Coax in 200 CM Length from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: [2.92mm Male to 2.92mm Female Cable Tinned Copper RG402 Type .141 Coax in 200 CM Length FMCA2918-200CM](#)

URL: <https://www.fairviewmicrowave.com/2.92mm-male-to-2.92mm-female-cable-tinned-copper-rg402-type-.141-coax-fmca2918-200cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

