

## N Female to N Female Cable RG401 Type .250 Coax in 200 CM

The type N female to type N female 200 cm cable using RG401 type .250 coax, part number FMCA3113-200CM, from Fairview Microwave is in-stock and ships same day. This Fairview type N to type N cable assembly has a female to female gender configuration with 50 ohm semi-rigid FM-SR250CU-STR coax. Fairview Microwave's semi-rigid RF cable assemblies are ideal for high performance applications and can be formed, using proper tooling, to the routing pattern required.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

### Electrical Specifications

| Description             | Min | Typ          | Max | Units        |
|-------------------------|-----|--------------|-----|--------------|
| Velocity of Propagation |     | 69.5         |     | %            |
| Capacitance             |     | 29.6 [97.11] |     | pF/ft [pF/m] |

### Mechanical Specifications

#### Cable Assembly

|         |                      |
|---------|----------------------|
| Length* | 78.74 in [200 cm]    |
| Weight  | 0.963 lbs [436.81 g] |

#### Cable

|                                      |                |
|--------------------------------------|----------------|
| Cable Type                           | FM-SR250CU-STR |
| Impedance                            | 50 Ohms        |
| Inner Conductor Type                 | Solid          |
| Inner Conductor Material and Plating | Copper, Silver |
| Dielectric Type                      | PTFE           |
| Number of Shields                    | 1              |
| Shield Layer 1                       | Copper         |

|                              |                   |
|------------------------------|-------------------|
| One Time Minimum Bend Radius | 0.25 in [6.35 mm] |
|------------------------------|-------------------|

#### Connectors

| Description             | Connector 1   | Connector 2   |
|-------------------------|---------------|---------------|
| Type                    | N Female      | N Female      |
| Impedance               | 50 Ohms       | 50 Ohms       |
| Body Material & Plating | Brass, Nickel | Brass, Nickel |

**Compliance Certifications** (see [product page](#) for current document)

### Plotted and Other Data

Notes:

- Values at 25°C, sea level.



### Configuration:

- N Female
- N Female
- FM-SR250CU-STR

### Features:

- 69.5% Phase Velocity

### Applications:

- General Purpose
- Laboratory Use

Fairview Microwave  
301 Leora Ln., Suite 100  
Lewisville, TX 75056  
Tel: 1-800-715-4396 / (972) 649-6678  
Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

## How to Order

Part Number Configuration:

**FMCA3113 - xx uu**

cm = Centimeters  
<blank> = Inches  
Length

Example: FMCA3113-12 = 12 inches long cable  
FMCA3113-100cm = 100 cm long cable

N Female to N Female Cable RG401 Type .250 Coax in 200 CM from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: [N Female to N Female Cable RG401 Type .250 Coax in 200 CM FMCA3113-200CM](#)

URL: <https://www.fairviewmicrowave.com/n-female-to-n-female-cable-rg401-type-.250-coax-fmca3113-200cm-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

