

RF PCB Connector, 75 Ohm Mini SMB Jack Connector Solder Attachment .062 inch End Launch PCB

75 Ohm Mini SMB jack connector with solder attachment for .062 inch end launch PCB, part number FMCN44131, from Fairview Microwave is in-stock and ships same day. This Mini SMB jack connector operates up to a maximum frequency of 2 GHz.

Fairview's 75 ohm Mini SMB jack connector FMCN44131 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	DC		2	GHz
Operating Voltage (AC)			335	Vrms
DWV (AC)			1,000	Vrms
High Potential Voltage at 4 and 7 MHz			600	Vrms
Insulation Resistance	1,000			MOhms

Mechanical Specifications


Size	
Length	0.562 in [14.27 mm]
Width/Dia.	0.25 in [6.35 mm]
Height	0.25 in [6.35 mm]
Weight	0.003 lbs [1.36 g]
Mating Cycles	500 Cycles

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold over Nickel 30 µin minimum
Insulation	PTFE	
Body	Brass	Gold over Nickel 10 µin minimum

Environmental Specifications

Temperature	
Operating Range	-65 to +165 deg C
Shock	MIL-STD-202, Method 213, Condition B



Configuration:

- Mini SMB Jack Connector
- MIL-C-39012
- 75 Ohms
- Straight Body Geometry
- .062 inch End Launch Interface Type
- Solder Attachment

Features:

- Operating Frequency of 2 GHz Max.
- Gold over Nickel Plated Beryllium Copper Contact
- 30 µin minimum contact plating

Applications:

- General Purpose Test
- Space Saving for PCB Applications

Fairview Microwave
301 Leora Ln., Suite 100
Lewisville, TX 75056
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Vibration
Thermal Shock
Salt Spray

MIL-STD-202, Method 204, Condition B
MIL-STD-202, Method 107, Condition B
MIL-STD-202, Method 101, Condition B

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

RF PCB Connector, 75 Ohm Mini SMB Jack Connector Solder Attachment .062 inch End Launch PCB from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [RF PCB Connector, 75 Ohm Mini SMB Jack Connector Solder Attachment .062 inch End Launch PCB FMCN44131](#)

URL: <https://www.fairviewmicrowave.com/mini-smb-jack-standard-0.062-end-launch-connector-fmcn44131-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

