

BMA Plug (Male) Bulkhead Connector Solder Attachment for FM-SR086ALTN-COIL, FM-SR086CU-COIL, FM-SR086CUTN-COIL, FM-SR086TB Cable



FMCN5151

Configuration

- BMA Plug Connector
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: FM-SR086ALTN-COIL, FM-SR086CU-COIL, FM-SR086CUTN-COIL, FM-SR086TB, FM-SR086TBJ, FM-F086
- Bulkhead

Features

- Operating Frequency of 18 GHz Max.
- Excellent VSWR of 1.25:1
- Blind Mate Connector
- Gold over Nickel over Copper Plated Beryllium Copper Contact

Applications

- General Purpose Test
- Rack and Panel Mount Applications
- Custom Cable Assemblies

Description

BMA Plug Bulkhead Standard Bulkhead Connector Solder Attachment for FM-SR086ALTN-COIL, FM-SR086CU-COIL, FM-SR086CUTN-COIL, FM-SR086TB, FM-SR086TBJ and FM-F086 Cable, part number FMCN5151, from Fairview Microwave is in-stock and ships same day. This BMA plug connector operates up to a maximum frequency of 18 GHz and offers excellent VSWR of 1.25:1. This blind mate connector is ideal for applications without direct visual or tactile access to the connection point, for example, when two circuit boards need to be mated. Fairview's FMCN5151 bulkhead BMA connector enables designers to make external connections on product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Fairview's BMA plug bulkhead connector FMCN5151 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.25:1	
Insertion Loss			0.127	dB
Operating Voltage (AC)			670	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Inner Conductor DC Resistance			2	mOhms
Outer Conductor DC Resistance			2	mOhms
Insulation Resistance	5,000			MOhms
Impedance		50		Ohms

Mechanical Specifications

Size

Length	0.689 in [17.5 mm]
Width	0.315 in [8 mm]
Height	0.315 in [8 mm]

BMA Plug (Male) Bulkhead Connector Solder Attachment for FM-SR086ALTN-COIL, FM-SR086CU-COIL, FM-SR086CUTN-COIL, FM-SR086TB Cable



FMCN5151

Weight	0.0062 lbs [2.81 g]
--------	---------------------

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold over Nickel over Copper
Insulation	PTFE	
Body	Brass	Gold over Nickel over Copper
Gasket	Silicone	
Washer	Brass	Gold over Nickel over Copper

Environmental Specifications

Temperature	
Operating Range	-65 to +165 deg C
Humidity	MIL-STD-202, Method 106
Thermal Shock	MIL-STD-202, Method 107, Condition B
Salt Spray	MIL-STD-202, Method 101, Condition B

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

BMA Plug (Male) Bulkhead Connector Solder Attachment for FM-SR086ALTN-COIL, FM-SR086CU-COIL, FM-SR086CUTN-COIL, FM-SR086TB Cable from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [BMA Plug \(Male\) Bulkhead Connector Solder Attachment for FM-SR086ALTN-COIL, FM-SR086CU-COIL, FM-SR086CUTN-COIL, FM-SR086TB Cable FMCN5151](#)

URL: <https://www.fairviewmicrowave.com/product/rf-connectors/bma-plug-fm-sr086altn-coil-fm-sr086cu-coil-fm-sr-086cutn-coil-fm-sr086tb-fm-sr086tbj-fm-f086-connector-fmcn5151.html>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMCN5151 CAD Drawing

BMA Plug (Male) Bulkhead Connector Solder Attachment for FM-SR086ALTN-COIL, FM-SR086CU-COIL, FM-SR086CUTN-COIL, FM-SR086TB Cable

