

# SMA Female Commercial Grade PCB Connector End Launch Thru Hole Solder Attachment



## **FMCN5206**

#### Configuration

- SMA Female Connector
- 50 Ohms
- · Straight Body Geometry

#### **Features**

· Operating Frequency of 18 GHz Max.

## **Applications**

· General Purpose Test

- · Connector Interface Types: End Launch Thru Hole
- · Commercial Grade Design
- · Gold Plated Beryllium Copper Contact
- PCB Applications

## **Description**

SMA Female Commercial Grade Connector Solder Attachment for End Launch Thru hole Cable, part number FMCN5206, from Fairview Microwave is in-stock and ships same day. This SMA female connector operates up to a maximum frequency of 18 GHz.

Fairview's SMA female connector FMCN5206 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

## **Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
Dielectric Withstanding Voltage (AC)			750	Vrms
Insulation Resistance	5,000			MOhms
Impedance		50		Ohms

### **Mechanical Specifications**

 Size

 Length
 0.7 in [17.78 mm]

 Width
 0.33 in [8.38 mm]

 Height
 0.33 in [8.38 mm]

 Weight
 0.00604 lbs [2.74 g]

 Mating Cycles
 100 Cycles

## **Material Specifications**

Description	Material	Plating
Contact	Beryllium Copper	Gold
Insulation	PTFE	
Body	Brass	Gold



# SMA Female Commercial Grade PCB Connector End Launch Thru Hole Solder Attachment



## **FMCN5206**

### **Environmental Specifications**

Temperature

Operating Range

-55 to +125 deg C

Compliance Certifications (see product page for current document)

#### **Plotted and Other Data**

Notes:

SMA Female Commercial Grade PCB Connector End Launch Thru Hole Solder Attachment from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: SMA Female Commercial Grade PCB Connector End Launch Thru Hole Solder Attachment FMCN5206

URL: https://www.fairviewmicrowave.com/sma-female-end-launch-thru-hole-pcb-connector-fmcn5206-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

