

N Female (Jack) Bulkhead Connector Crimp/Solder Attachment for LMR-400, LMR-400-DB, LMR-400-FR, LMR-400-LLPX Cable, .640 inch DD Hole



FMCN5286

Configuration

- N Female Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: LMR-400, LMR-400-DB, LMR-400-FR, LMR-400-LLPX, LMR-400-UF, LMR-400-UF-FR, LMR-LW400, TCOM-400, TCOM-400-FR
- Bulkhead

Features

- Operating Frequency of 11 GHz Max.
- Good VSWR of 1.3:1
- Gold Plated Brass Contact
- 30 µin minimum contact plating

Applications

- General Purpose Test
- Rack and Panel Mount Applications
- Custom Cable Assemblies

Description

Type N Female Bulkhead Standard Bulkhead Connector Crimp/Solder Attachment for LMR-400, LMR-400-DB, LMR-400-FR, LMR-400-LLPX, LMR-400-UF, LMR-400-UF-FR, LMR-LW400, TCOM-400 and TCOM-400-FR Cable, part number FMCN5286, from Fairview Microwave is in-stock and ships same day. This type N female connector operates up to a maximum frequency of 11 GHz and offers good VSWR of 1.3:1. Fairview's FMCN5286 bulkhead type N connector enables designers to make external connections on product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Fairview's type N female bulkhead connector FMCN5286 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz
VSWR			1.3:1	
Operating Voltage (AC)			1,500	Vrms
Dielectric Withstanding Voltage (AC)			2,500	Vrms
Inner Conductor DC Resistance			1	mOhms
Outer Conductor DC Resistance			1	mOhms
Insulation Resistance	5,000			MOhms
RF Leakage	90			dB
Impedance		50		Ohms

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 10					GHz
Insertion Loss, Max	0.15					dB

N Female (Jack) Bulkhead Connector Crimp/Solder Attachment for LMR-400, LMR-400-DB, LMR-400-FR, LMR-400-LLPX Cable, .640 inch DD Hole



FMCN5286

Mechanical Specifications

Size

Length	1.72 in [43.69 mm]
Width	0.87 in [22.1 mm]
Height	0.87 in [22.1 mm]
Weight	0.09 lbs [40.82 g]
Mating Cycles	500 Cycles

Material Specifications

Description	Material	Plating
Contact	Brass	Gold 30 µin minimum
Insulation	PTFE	
Body	Brass	Tri-Metal

Environmental Specifications

Temperature

Operating Range	-65 to +165 deg C
Vibration	MIL-STD-202, Method 204, Condition B
Temperature Cycle	MIL-STD-202, Method 107, Condition B
Salt Spray	MIL-STD-202, Method 101, Condition B

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

N Female (Jack) Bulkhead Connector Crimp/Solder Attachment for LMR-400, LMR-400-DB, LMR-400-FR, LMR-400-LLPX Cable, .640 inch DD Hole from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [N Female \(Jack\) Bulkhead Connector Crimp/Solder Attachment for LMR-400, LMR-400-DB, LMR-400-FR, LMR-400-LLPX Cable, .640 inch DD Hole FMCN5286](#)

URL: <https://www.fairviewmicrowave.com/n-female-lmr-400-lmr-400-db-lmr-400-fr-lmr-400-llpx-lmr-400-uf-lmr-400-uf-fr-lmr-lw400-tcom-400-tcom-400-fr-connector-fmcn5286-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMCN5286 CAD Drawing

N Female (Jack) Bulkhead Connector Crimp/Solder Attachment for LMR-400, LMR-400-DB, LMR-400-FR, LMR-400-LLPX Cable, .640 inch DD Hole

