

RA BNC Male (Plug) Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, LMR- 240-UF, LMR-LW240, RG8X, TCOM-240 Cable



FMCN5294

Configuration

- BNC Male Connector
- 50 Ohms
- Right Angle Body Geometry
- Connector Interface Types: LMR-240, LMR-240-DB, LMR-240-FR, LMR-240-UF, LMR-LW240, RG8X, TCOM-240, TCOM-240-FR

Features

- Operating Frequency of 4 GHz Max.
- Gold Plated Brass Contact

Applications

- General Purpose Test
- Custom Cable Assemblies

Description

RA BNC Male Standard Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, LMR-240-UF, LMR-LW240, RG8X, TCOM-240 and TCOM-240-FR Cable, part number FMCN5294, from Fairview Microwave is in-stock and ships same day. This BNC male connector operates up to a maximum frequency of 4 GHz. Its right angle body geometry facilitates connections in tight spaces.

Fairview's RA BNC male connector FMCN5294 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		4	GHz
Impedance		50		Ohms

Mechanical Specifications

Size

Length	1.095 in [27.81 mm]
Width	0.57 in [14.48 mm]
Height	1.052 in [26.72 mm]
Weight	0.047 lbs [21.32 g]

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Nickel
Coupling Nut	Brass	Nickel

RA BNC Male (Plug) Connector Crimp/Solder Attachment
for LMR-240, LMR-240-DB, LMR-240-FR, LMR-
240-UF, LMR-LW240, RG8X, TCOM-240 Cable



FMCN5294

Environmental Specifications

Temperature

Operating Range -40 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

RA BNC Male (Plug) Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, LMR-240-UF, LMR-LW240, RG8X, TCOM-240 Cable from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [RA BNC Male \(Plug\) Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, LMR-240-UF, LMR-LW240, RG8X, TCOM-240 Cable FMCN5294](#)

URL: <https://www.fairviewmicrowave.com/bnc-male-lmr-240-lmr-240-db-lmr-240-fr-lmr-240-uf-lmr-lw240-rg8x-tcom-240-tcom-240-fr-connector-fmcn5294-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMCN5294 CAD Drawing

RA BNC Male (Plug) Connector Crimp/Solder Attachment for LMR-240, LMR-240-DB, LMR-240-FR, LMR-240-UF, LMR-LW240, RG8X, TCOM-240 Cable

