

1.00 mm Female (Jack) 2 Hole PCB Narrow Body, 0.0866 Inches End Launch PCB Connector, Solderless



FMCN5372

Configuration

- 1.0mm Female Connector
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: End Launch
- 2 Hole Flange

Features

- Operating Frequency of 110 GHz Max.
- Good VSWR of 2:1
- Gold Plated Beryllium Copper Contact

Applications

- General Purpose Test
- Rack and Panel Mount Applications
- PCB Applications

Description

1.00 mm Female (Jack) 2 Hole End Launch PCB Connector, part number FMCN5372, from Fairview Microwave is in-stock and ships same day. This 1.0mm female connector operates up to a maximum frequency of 110 GHz and offers good VSWR of 2:1. Fairview's FMCN5372 2 hole flange 1.0mm connector enables designers to make external connections on product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Fairview's 1.0mm female 2 hole flange connector FMCN5372 datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		110	GHz
VSWR			2:1	
Impedance		50		Ohms

Mechanical Specifications

Size

Length	0.644 in [16.36 mm]
Width	0.311 in [7.9 mm]
Height	0.295 in [7.49 mm]
Weight	0.0095 lbs [4.31 g]
Mating Cycles	500 Cycles

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold
Insulation	PTFE	
Body	Passivated Stainless Steel	

1.00 mm Female (Jack) 2 Hole PCB Narrow Body, 0.0866 Inches End Launch PCB Connector, Solderless



FMCN5372

Environmental Specifications

Temperature

Operating Range

-40 to +125 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

1.00 mm Female (Jack) 2 Hole PCB Narrow Body, 0.0866 Inches End Launch PCB Connector, Solderless from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [1.00 mm Female \(Jack\) 2 Hole PCB Narrow Body, 0.0866 Inches End Launch PCB Connector, Solderless FMCN5372](#)

URL: <https://www.fairviewmicrowave.com/product/rf-connectors/1.0mm-female-end-launch-pcb-connector-fmcn5372.html>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMCN5372 CAD Drawing

1.00 mm Female (Jack) 2 Hole PCB Narrow Body, 0.0866 Inches End Launch PCB Connector, Solderless

