

## 8 dBi Omni Antenna 698-960 MHz N Type Connector

The 5G /LTE outdoor omnidirectional FM510M1035 antenna from Fairview Microwave is a high performance RF component which operates from 698 to 960 MHz. The FM510M1035 antenna is ideal for 5G, LTE, CDMA, LPWAN/IoT/M2M applications including LoRA, LTE-M, and NB-IOT. The Multi-Band design of the Fairview Microwave FM510M1035 antenna can be used for a wide array of cellular telecommunication wireless applications where wide coverage is desired. Fairview Microwave's FM510M1035 can be used to distribute Cellular signals throughout an outdoor area.

The Type N connectorized FM510M1035 antenna with vertical polarization from Fairview Microwave provides excellent outdoor coverage for all base station applications. The Type N connectorized FM510M1035 antenna from Fairview Microwave excels in large open areas. The mounting bracket and hardware are included for easy installation. Fairview Microwave 5G / LTE outdoor omnidirectional with Type N female purchases will ship the same day. Our FM510M1035 antenna is part of over one million RF, microwave and millimeter wave components in stock and ready for same-day shipment worldwide.

### Configuration

Design	Omni
Polarization	Vertical
Connector Type	N Female
Number of Ports	1

### Electrical Specifications

Description	Min	Typ	Max	Units
Frequency Range	698		960	MHz
Impedance		50		Ohms
Gain		8		dBi
Input Power			50	Watts
VSWR			2:1	

### Mechanical Specifications

Radome Material	Polycarbonate
<b>Size</b>	
Length	35 in [889 mm]
Width	3.1 in [78.74 mm]
Mounting Mast Diameter	1.97 to 3.54 in [50.04 to 89.92 mm]
Weight	4.19 lbs [1.9 kg]

### Environmental Specifications

<b>Temperature</b>	
Operating Range	-40 to +70 deg C
Wind Loading	124.27 MPH [199.99 KPH]
Humidity	91



### Features:

- All weather operation
- Includes heavy duty steel mast mounting brackets
- Lightweight polycarbonate radome
- Integral N-Female connector
- Commercial grade design
- 360° Omnidirectional Pattern
- 6 to 8 dBi gain

### Applications:

- Supports lowband LTE and 5G networks
- Point to Multipoint and Non Line of Sight (NLOS) Applications
- 600, 700, 800 Cellular Band Operation

Fairview Microwave  
 301 Leora Ln., Suite 100  
 Lewisville, TX 75056  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

8 dBi Omni Antenna 698-960 MHz N Type Connector from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [8 dBi Omni Antenna 698-960 MHz N Type Connector FM510M1035](#)

URL: <https://www.fairviewmicrowave.com/antenna-8-dbi-n-female-fm51om1035-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

