

## 5 dB Fixed Attenuator N Male (Plug) to N Female (Jack) DC to 12 GHz Rated to 2 Watts, Brass Body, 1.35:1 VSWR



### FMAT7468-5

#### Features

- DC to 12 GHz Frequency Range
- N Connectorized Design
- Attenuation 5 dB  $\pm$ 1 dB
- Max Power 2 Watts (CW)
- Max VSWR of 1.35:1

#### Applications

- Instrumentation
- Precision Measurements
- Prototyping and Characterization
- Production Systems
- WIFI 6E
- 5G Cellular bands

#### Description

Fairview Microwave carries a wide range of fixed attenuators with a broad selection of attenuation levels, frequency ranges, and power dissipation ranges. RF microwave attenuators (also known as RF pads) lower the amplitude of a signal (attenuate) a known amount and can be used in a wide variety of applications. These attenuator pads are used when a signal needs to be reduced to protect measurement equipment or other circuitry, to extend the range of power meters and amplifiers, and to impedance match circuits by reducing the VSWR seen by adjacent components. RF attenuators can prevent signal overload in amplifiers, receivers and detectors, adjusting the signal level to a range that is optimal.

Few RF components are as commonly used as fixed coaxial attenuators, and Fairview Microwave carries one of the largest in-stock varieties and ships them same day. The 5 dB Fixed Attenuator FMAT7468-5 is rated to and operates from DC to 12 GHz. The versatile coaxial package uses N female to N male connectors.

#### Electrical Specifications

| Description         | Minimum | Typical | Maximum | Units |
|---------------------|---------|---------|---------|-------|
| Frequency Range     | DC      |         | 12      | GHz   |
| Impedance           |         | 50      |         | Ohms  |
| Nominal Attenuation |         | 5       |         | dB    |
| VSWR                |         |         | 1.35:1  |       |
| Input Power, CW     |         |         | 2       | Watts |

#### Specifications by Frequency

| Description               | F1      | F2     | F3      | F4       | F5 | Units |
|---------------------------|---------|--------|---------|----------|----|-------|
| Frequency Range           | DC to 2 | 2 to 5 | 5 to 10 | 10 to 12 |    | GHz   |
| VSWR, Max                 | 1.15:1  | 1.25:1 | 1.35:1  | 1.35:1   |    |       |
| Attenuation Accuracy, Typ | 0.2     | 0.3    | 0.5     | 1        |    | dB    |

#### Mechanical Specifications

##### Size

|                           |                     |
|---------------------------|---------------------|
| Length                    | 2.1 in [53.34 mm]   |
| Width/Diameter            | 0.827 in [21.01 mm] |
| Height                    | 0.827 in [21.01 mm] |
| Weight                    | 0.09 lbs [40.82 g]  |
| Body Material and Plating | Brass, Tri-Metal    |

## 5 dB Fixed Attenuator N Male (Plug) to N Female (Jack) DC to 12 GHz Rated to 2 Watts, Brass Body, 1.35:1 VSWR



### FMAT7468-5

#### Configuration

|               |                       |
|---------------|-----------------------|
| Design        | Fixed, Bi-Directional |
| Package Style | Conectorized          |

#### Connectors

| Description                  | Connector 1            | Connector 2            |
|------------------------------|------------------------|------------------------|
| Type                         | N Female               | N Male                 |
| Contact Material and Plating | Beryllium Copper, Gold | Beryllium Copper, Gold |
| Dielectric Type              | Teflon                 | Teflon                 |
| Body Material and Plating    | Brass, Tri-Metal       | Brass, Tri-Metal       |

#### Environmental Specifications

##### Temperature

#### Compliance Certifications (see [product page](#) for current document)

#### Plotted and Other Data

Notes:

#### Typical Performance Data

5 dB Fixed Attenuator N Male (Plug) to N Female (Jack) DC to 12 GHz Rated to 2 Watts, Brass Body, 1.35:1 VSWR from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [5 dB Fixed Attenuator N Male \(Plug\) to N Female \(Jack\) DC to 12 GHz Rated to 2 Watts, Brass Body, 1.35:1 VSWR FMAT7468-5](#)

URL: <https://www.fairviewmicrowave.com/5db-fixed-attenuator-n-female-n-male-2-watts-fmat7468-5-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

FMAT7468-5 CAD Drawing

5 dB Fixed Attenuator N Male (Plug) to N Female (Jack) DC to 12 GHz  
Rated to 2 Watts, Brass Body, 1.35:1 VSWR

