

## FMCA2764-100CM DATA SHEET

# TNC Male Right Angle to TNC Male Right Angle Cable in 100 CM Length Using RG223 Coax

The RA TNC male to RA TNC male cable using RG223 coax, part number FMCA2764-100CM, from Fairview Microwave is in-stock and ships same day. This Fairview TNC to TNC cable assembly has a male to male gender configuration with 50 ohm flexible RG223 coax. Fairview Microwave's flexible RF cable assemblies are ideal for applications where tight bends and continual flexure are required. The FMCA2764-100CM TNC male to TNC male cable assembly operates to 3 GHz. The right angle TNC interfaces on the RG223 cable allow for easier connections in tight spaces. The double shielding of this Fairview cable assembly provides excellent shielding effectiveness.

Custom versions of most RF cable assemblies can be built and shipped same day. Custom cable assembly lengths can be obtained by specifying the desired length on the web site at time of order or by contacting a sales representative. Other RF cable assembly value added services including connector orientation or clocking, heat shrink booting and labeling are also available. RF testing can also be performed to document the electrical performance of your cable assembly.

## **Electrical Specifications**

Min	Т	ур	Max	U	nits
DC			3	(	GHz
	6	6			%
,	]	pF/ft [pF/m]			
			500	V	rms
	DC	DC 6	DC 66	DC 3 66 30.8 [101.05]	DC 3 0 66 30.8 [101.05] pF/ft

## **Performance by Frequency**

Description	F1	F2	F3	F4	F5	Units
Frequency	0.1	0.25	0.5	1	3	GHz
Insertion Loss (Typ.)	0.54	0.61	0.7	0.84	1.22	dB/ft
	1.77	2	2.3	2.76	4	dB/m

**Electrical Specification Notes:** 

The Insertion Loss data above is based on the performance specifications of the coax and connectors used in this assembly. The Insertion Loss includes an estimated insertion loss of 0.2 dB per connector.

#### **Mechanical Specifications**

#### **Cable Assembly**

Length\* 39.37 in [100 cm] Weight 0.2468 lbs [111.95 g]

## Cable

Cable Type
Impedance
Inner Conductor Type
Inner Conductor Material and Plating
Dielectric Type
Number of Shields
Shield Layer 1

RG223 50 Ohms Solid Copper, Silver

PE 2

Silver Plated Copper Braid



## **Configuration:**

- TNC Male Right Angle
- TNC Male Right Angle
- RG223

## **Features:**

- Max Frequency 3 GHz
- 66% Phase Velocity
- Double Shielded
- PVC Jacket

## **Applications:**

- General Purpose
- · Laboratory Use

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com

sales@fairviewmicrowave.com





Shield Layer 2 Jacket Material Jacket Diameter Silver Plated Copper Braid

PVC, Black

0.21 in [5.33 mm]

One Time Minimum Bend Radius

1 in [25.4 mm]

## **Connectors**

Description	Connector 1	Connector 2
Туре	TNC Male	TNC Male
Specification	MIL-STD-348A	MIL-STD-348A
Impedance	50 Ohms	50 Ohms
Contact Material & Plating	Brass, Gold	Brass, Gold
Contact Plating Spec.	30μ in. minimum	30µ in. minimum
Dielectric Type	Teflon	Teflon
Body Material & Plating	Brass, Nickel	Brass, Nickel
Body Plating Spec.	100μ in. minimum	n 100µ in. minimum
Coupling Nut Material & Pla	iting Brass, Nickel	Brass, Nickel
Coupling Nut Plating Spec.	100μ in. minimum	100µ in. minimum

**Compliance Certifications** (see product page for current document)

## **Plotted and Other Data**

Notes:

• Values at 25°C, sea level.

#### **How to Order**

Part Number Configuration:

FMCA2764 - xx uu

cm = Centimeters
<br/>
<br/>
<br/>
clank> = Inches

Length

Example: FMCA2764-12 = 12 inches long cable
 FMCA2764-100cm = 100 cm long cable





TNC Male Right Angle to TNC Male Right Angle Cable in 100 CM Length Using RG223 Coax from Fairview Microwave has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link to obtain additional part information: TNC Male Right Angle to TNC Male Right Angle Cable in 100 CM Length Using RG223 Coax FMCA2764-100CM

URL: https://www.fairviewmicrowave.com/ra-tnc-male-to-ra-tnc-male-cable-rg223-coax-in-100-cm-and-rohs-fmca2764-100cm-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order

	ent improve												
	specificatio												
	of the part					ır purpose	, and Fair	view M	1icrowav	e does	not ass	sume ar	ny liability
arising ou	t of the use	of any p	part or do	ocument	tation.								



# FMCA2764-100CM DATA SHEET

