

75 Ohm 1.0/2.3 Jack Bulkhead Push-On PCB Connector End Launch Solder Attachment

Fairview Microwave's 75 Ohm DIN 1.0/2.3 connectors have a secure quick-locking push/pull design creating a convenient fastened connection. These 75 Ohm 1.0-2.3 DIN connectors operate to 3 GHz, making them an excellent choice for many data communications and video applications, including 3G video. The small size and push/pull connection method allows for a dense connector-to-connector footprint, saving valuable space in panels and other applications requiring a high number of interconnects. These durable RF connectors also have a mating life of up to 500 connections.

Electrical Specifications

| Description | Min | Typ | Max | Units |
|-----------------|-----|-----|--------|-------|
| Frequency Range | DC | | 3 | GHz |
| VSWR | | | 1.15:1 | |

Mechanical Specifications

| | |
|-------------|---------------------|
| Size | |
| Length | 0.647 in [16.43 mm] |
| Width/Dia. | 0.287 in [7.29 mm] |
| Weight | 0.0072 lbs [3.27 g] |

Material Specifications

| Description | Material | Plating |
|-----------------|------------------|---------|
| Contact | Beryllium Copper | Gold |
| Insulation | PTFE | |
| Outer Conductor | Brass | Gold |
| Body | Brass | Gold |
| Washer | Brass | Gold |



Configuration:

- Push-On 1.0/2.3 Jack Connector
- 75 Ohms
- Straight Body Geometry
- End Launch Interface Type
- Solder Attachment
- Bulkhead

Features:

- Push/Pull connection design
- Secure locking mechanism
- No torque tools required
- Performance to 3 GHz
- 500 Mating cycles

Applications:

- 3G SDI Video
- 75 Ohm Switching Equipment
- Communication systems

Fairview Microwave
1130 Junction Dr. #100
Allen, TX 75013
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Environmental Specifications

Temperature

Operating Range -65 to 165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data


Notes:

75 Ohm 1.0/2.3 Jack Bulkhead Push-On PCB Connector End Launch Solder Attachment from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [75 Ohm 1.0/2.3 Jack Bulkhead Push-On PCB Connector End Launch Solder Attachment FMCN1115](#)

URL: <https://www.fairviewmicrowave.com/1.0-2.3-jack-push-on-end-launch-pcb-connector-fmcn1115-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



| | | | | | |
|---|--------|---|-------|---------------------------|-------------|
| FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM | | NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm]. | | | |
| TITLE 75 Ohm 1.0/2.3 Jack Bulkhead Push-On PCB Connector End Launch Solder Attachment | | DWG NO FMCN1115 | | CAGE CODE 3FKR5 | |
| CAD FILE | 070116 | SHEET | SCALE | N/A | SIZE A 2233 |