

Transfer Failsafe Electro-Mechanical Relay Switch From DC to 12.4 GHz, 160 Watts, N

The FMSW6174 is a Transfer Electromechanical Relay Switch that operates over a wide frequency band from DC to 12.4 GHz and has a rating of 160 Watts input power (CW). Rated for 1M life cycles for high reliability operation, this design uses a Failsafe Actuator with a break before make configuration. The switch exhibits exceptional electrical performance specified from 0.2 dB max for insertion loss and 80 dB min for isolation, and guaranteed over -25°C to +65°C. The assembly requires an operating voltage of +12Vdc. External connectors include solder terminals and N female connectors.

Electrical Specifications

Switch Type Transfer, Reflective
Actuator Type Failsafe
Switching Sequence Break Before Make

Description	Min	Typ	Max	Units
Frequency Range	DC		12.4	GHz
Impedance		50		Ohms
Operating Voltage		12		Volts
Actuating Current @ 12 Volts		540		mA
VSWR			1.45:1	
Insertion Loss			0.4	dB
Isolation	60			dB
Input Power (CW) (at 12.4 GHz)			160	Watts

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC - 4	4 - 8	8 - 12.4			GHz
VSWR, Max	1.2:1	1.3:1	1.45:1			
Insertion Loss, Max	0.2	0.3	0.4			dB
Isolation, Min	80	70	60			dB

Mechanical Specifications

Size
Length 2.06 in [52.32 mm]
Width/Diameter 2 in [50.8 mm]
Height 2 in [50.8 mm]
Weight 0.875 lbs [396.89 g]
Body Material and Plating Aluminum
Package Type Connectorized Module
Operating Life 1,000,000 Cycles
Switching Time 50 ms Max



Features:

- Transfer Relay Switch
- DC to 12.4 GHz Frequency Range
- 1M Cycle Operating Life Min
- Failsafe Actuator
- Insertion Loss 0.4 dB max
- Isolation 60 dB min
- 160 Watts Avg Power Max
- Switching Sequence Break Before Make

Applications:

- Test & Measurement
- Communications System
- Instrumentation

Fairview Microwave
1130 Junction Dr. #100
Allen, TX 75013
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Connectors

RF Connector Type	N Female
RF Connector Contact Material & Plating	Beryllium Copper, Gold
RF Connector Body Material & Plating	Passivated Stainless Steel
Control Connector	Solder Pin

Environmental Specifications

Temperature

Operating Range	-25 to +65 deg C
ESD Sensitivity	ESD Sensitive Material. Transport material in Approved ESD bags. Handle in approved ESD Workstation.



Environmental Specification Notes:
 Designed to Meet MIL-DTL-3928



Compliance Certifications (visit www.FairviewMicrowave.com for current document)


Not RoHS Compliant

Plotted and Other Data

Notes:

Typical Performance Data






Transfer Failsafe Electro-Mechanical Relay Switch From DC to 12.4 GHz, 160 Watts, N from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [Transfer Failsafe Electro-Mechanical Relay Switch From DC to 12.4 GHz, 160 Watts, N FMSW6174](http://www.fairviewmicrowave.com/transfer-failsafe-electro-mechanical-relay-switch-fmsw6174-p.aspx)


URL: <http://www.fairviewmicrowave.com/transfer-failsafe-electro-mechanical-relay-switch-fmsw6174-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



* THESE DIMENSIONS AND TOLERANCES
SUPERSEDE NOTE #1 ON TITLE BLOCK.

FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].			
TITLE Transfer Failsafe Electro-Mechanical Relay Switch From DC to 12.4 GHz, 160 Watts, N		DWG NO FMSW6174		CAGE CODE 3FKR5	
CAD FILE	042815	SHEET	SCALE	N/A	SIZE A 2233



<div>FAIRVIEW MICROWAVE INC.</div> <div>ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM</div>	<div>NOTES:</div> <div>1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.</div> <div>2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.</div> <div>3. DIMENSIONS ARE IN INCHES [mm].</div>				
<div>TITLE</div> <div>Transfer Failsafe Electro-Mechanical Relay Switch From DC to 12.4 GHz, 160 Watts, N</div>	<div>DWG NO</div> <div>FMSW6174</div>		<div>CAGE CODE</div> <div>3FKR5</div>		
	<div>CAD FILE</div> <div>042815</div>	<div>SHEET</div> <div></div>	<div>SCALE</div> <div>N/A</div>	<div>SIZE</div> <div>A</div>	<div></div> <div>2233</div>