

## SP6T Normally Open Electro-Mechanical Relay Switch From DC to 10 GHz, 160 Watts, N

The FMSW6194 is an SP6T Electromechanical Relay Switch that operates over a wide frequency band from DC to 10 GHz and has a rating of 160 Watts input power (CW). Rated for 1M life cycles for high reliability operation, this design uses a Normally Open Actuator with a break before make configuration. The switch exhibits exceptional electrical performance specified from 0.25 dB max for insertion loss and 80 dB min for isolation, and guaranteed over -25°C to +65°C. The assembly requires an operating voltage of +12Vdc. External connectors include solder terminals and N female connectors.

### Electrical Specifications

|                    |                   |
|--------------------|-------------------|
| Switch Type        | SP6T, Reflective  |
| Actuator Type      | Normally Open     |
| Switching Sequence | Break Before Make |

| Description                     | Min | Typ | Max   | Units |
|---------------------------------|-----|-----|-------|-------|
| Frequency Range                 | DC  |     | 10    | GHz   |
| Impedance                       |     | 50  |       | Ohms  |
| Operating Voltage               |     | 12  |       | Volts |
| Actuating Current @ 12 Volts    |     | 255 |       | mA    |
| VSWR                            |     |     | 1.6:1 |       |
| Insertion Loss                  |     |     | 0.6   | dB    |
| Isolation                       | 60  |     |       | dB    |
| Input Power (CW)<br>(at 10 GHz) |     |     | 160   | Watts |

### Performance by Frequency

| Description         | F1     | F2    | F3     | F4 | F5 | Units |
|---------------------|--------|-------|--------|----|----|-------|
| Frequency Range     | DC - 4 | 4 - 8 | 8 - 10 |    |    | GHz   |
| VSWR, Max           | 1.25:1 | 1.4:1 | 1.6:1  |    |    |       |
| Insertion Loss, Max | 0.25   | 0.4   | 0.6    |    |    | dB    |
| Isolation, Min      | 80     | 70    | 60     |    |    | dB    |

### Mechanical Specifications

|                           |                      |
|---------------------------|----------------------|
| <b>Size</b>               |                      |
| Length                    | 2.3 in [58.42 mm]    |
| Width/Diameter            | 2.47 in [62.74 mm]   |
| Height                    | 2.47 in [62.74 mm]   |
| Weight                    | 1.156 lbs [524.35 g] |
| Body Material and Plating | Aluminum             |
| Package Type              | Connectorized Module |
| Operating Life            | 1,000,000 Cycles     |
| Switching Time            | 50 ms Max            |



### Features:

- Single Pole Six Throw Relay Switch
- DC to 10 GHz Frequency Range
- 1M Cycle Operating Life Min
- Normally Open Actuator
- Insertion Loss 0.6 dB max
- Isolation 60 dB min
- 160 Watts Avg Power Max
- Switching Sequence Break Before Make

### Applications:

- Test & Measurement
- Communications System
- Instrumentation

Fairview Microwave  
1130 Junction Dr. #100  
Allen, TX 75013  
Tel: 1-800-715-4396 / (972) 649-6678  
Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

**Connectors**

|                                         |                            |
|-----------------------------------------|----------------------------|
| RF Connector Type                       | N Female                   |
| RF Connector Contact Material & Plating | Beryllium Copper, Gold     |
| RF Connector Body Material & Plating    | Passivated Stainless Steel |
| Control Connector                       | Solder Pin                 |

**Environmental Specifications**

**Temperature**

|                 |                                                                                                      |
|-----------------|------------------------------------------------------------------------------------------------------|
| Operating Range | -25 to +65 deg C                                                                                     |
| ESD Sensitivity | ESD Sensitive Material. Transport material in Approved ESD bags. Handle in approved ESD Workstation. |



Environmental Specification Notes:  
 Designed to Meet MIL-DTL-3928



**Compliance Certifications** (visit [www.FairviewMicrowave.com](http://www.FairviewMicrowave.com) for current document)


Not RoHS Compliant

**Plotted and Other Data**

Notes:

**Typical Performance Data**






SP6T Normally Open Electro-Mechanical Relay Switch From DC to 10 GHz, 160 Watts, N from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [SP6T Normally Open Electro-Mechanical Relay Switch From DC to 10 GHz, 160 Watts, N FMSW6194](http://www.fairviewmicrowave.com/sp6t-normally-open-electro-mechanical-relay-switch-fmsw6194-p.aspx)


URL: <http://www.fairviewmicrowave.com/sp6t-normally-open-electro-mechanical-relay-switch-fmsw6194-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



\* THESE DIMENSIONS AND TOLERANCES SUPERSEDE NOTE #1 ON TITLE BLOCK.

|                                                                                                |        |                                                                                                                                                                                     |       |                    |             |
|------------------------------------------------------------------------------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------------------|-------------|
| <b>FAIRVIEW MICROWAVE INC.</b><br>ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM                    |        | NOTES:<br>1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.<br>2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.<br>3. DIMENSIONS ARE IN INCHES [mm]. |       |                    |             |
| TITLE<br>SP6T Normally Open Electro-Mechanical Relay Switch<br>From DC to 10 GHz, 160 Watts, N |        | DWG NO<br>FMSW6194                                                                                                                                                                  |       | CAGE CODE<br>3FKR5 |             |
| CAD FILE                                                                                       | 051215 | SHEET                                                                                                                                                                               | SCALE | N/A                | SIZE A 2233 |



SCHEMATIC NORMALLY OPEN SHOWN IN DE-ENERGIZED POSITION

|                                                                                                |  |  |  |                                                                                                                                                                                     |        |           |       |
|------------------------------------------------------------------------------------------------|--|--|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-----------|-------|
| FAIRVIEW MICROWAVE INC.<br>ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM                           |  |  |  | NOTES:<br>1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.<br>2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.<br>3. DIMENSIONS ARE IN INCHES [mm]. |        |           |       |
| TITLE<br>SP6T Normally Open Electro-Mechanical Relay Switch<br>From DC to 10 GHz, 160 Watts, N |  |  |  | DWG NO                                                                                                                                                                              |        | CAGE CODE |       |
|                                                                                                |  |  |  | FMSW6194                                                                                                                                                                            |        | 3FKR5     |       |
|                                                                                                |  |  |  | CAD FILE                                                                                                                                                                            | 051215 | SHEET     | SCALE |