

WR-650 Waveguide Standard Gain Horn Antenna Operating From 1.13 GHz to 1.73 GHz, 15 dBi Gain with CPR-650F Flange

The FMWAN650-15 standard horn antenna (also known as waveguide horn) from Fairview is part of our comprehensive selection of waveguide antennas. This WR-650 waveguide horn features an CPR-650F waveguide flange and operates from 1130 to 1730 MHz.

Our FMWAN650-15 standard gain horn antenna has a nominal gain of 15 dBi with a typical input VSWR of 1.5:1. Fairview's waveguide horns are available in 10, 15, and 20 dBi models with varying frequency ranges to suit the application needs.

Waveguide antennas, such as the FMWAN650-15 are used in a wide variety of applications due to the high-power handling capability, low loss, high directivity, and near constant electrical performance. Our WR-650 waveguide antennas with are part of over 40,000 RF, microwave, and millimeter wave components from Fairview available worldwide and Ship same day.

Configuration

Design	WR-650 Standard Gain Horn
Pattern	Directional
Polarization	Linear

Electrical Specifications


Description	Min	Typ	Max	Units
Frequency Range	1.13		1.73	GHz
Nominal Gain		15		dBi
Horizontal 3dB Beam Width		30		Deg
Vertical 3dB Beam Width		30		Deg
VSWR			1.5:1	

Mechanical Specifications

Size	
Length	16.9 in [429.26 mm]
Width/Diameter	21.7 in [551.18 mm]
Height	15 in [381 mm]
Weight	9.702 lbs [4.4 kg]

Waveguide Interface

Waveguide Size	WR-650
Flange Type	CPR-650F
Body Material and Plating	Aluminum



Features:

- 1130 MHz to 1730 MHz
- Linearly Polarized
- 15 dBi Nominal Gain
- WR-650 with CPR-650F Flange
- Powder Coated Aluminum

Applications:

- Antenna Measurements
- Wireless Communication
- Laboratory Use
- Microwave Testing
- Radome Testing
- EMC measurement
- Satellite Antenna Testing

Compliance Certifications (see [product page](#) for current document)


Plotted and Other Data

Notes:


Fairview Microwave
301 Leora Ln., Suite 100
Lewisville, TX 75056
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Typical Performance Data

Gain VS Frequency Curve:



Typical Pattern:



WR-650 Waveguide Standard Gain Horn Antenna Operating From 1.13 GHz to 1.73 GHz, 15 dBi Gain with CPR-650F Flange from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [WR-650 Waveguide Standard Gain Horn Antenna Operating From 1.13 GHz to 1.73 GHz, 15 dBi Gain with CPR-650F Flange FMWAN650-15](https://www.fairviewmicrowave.com/wr-650-waveguide-standard-gain-horn-antenna-operating-from-1.13-ghz-to-1.73-ghz-15-dbi-gain-with-cpr-650f-flange-fmwan650-15-p.aspx)

URL: <https://www.fairviewmicrowave.com/wr-650-waveguide-standard-gain-horn-antenna-operating-from-1.13-ghz-to-1.73-ghz-15-dbi-gain-with-cpr-650f-flange-fmwan650-15-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

