

Times Microwave LMR-200 Low Loss Flexible Coax Cable Black PF Jacket



LMR-200



Times Microwave Systems Connector Specification

Configuration

- · Low Loss, Outdoor Flexible Cable
- 2 Shield(s)

Features

- · Max Operating Frequency of 8 GHz
- Low Loss Cable

· Phase Velocity 83% VoP

Applications

· Laboratory Applications

General Purpose RF Interconnect

Description

LMR-200 coax cable from Fairview is only one of a large number of radio frequency twinaxial and coaxial cable types specifically stocked to be ready for quick shipment. Fairview Microwave LMR-200 coax cable is manufactured in a flexible design and has a 50 Ohm impedance. This low loss flexible 50 Ohm coax cable LMR-200 is constructed with a 0.195 inch diameter and PE jacket.

LMR-200 flexible 50 Ohm coax cable with PE jacket is rated for a 8 GHz maximum operating frequency. This 50 Ohm 0.195 inch diameter and low loss flexible coax cable is built with a shield count of 2 and RF shielding of 90 dB.

Fairview Microwave LMR-200 coax is constructed with PE (F) dielectric and a maximum operating temperature of 85 degrees C. Times Microwave LMR-200 coax cable specs for this wire properties can be found on its RF coax cable LMR-200 datasheet PDF specifications above.

LMR-200 cable is part of more than one million RF, microwave and millimeter wave parts in stock at Fairview. This Times Microwave low loss LMR-200 coax cable is ready to buy and can be shipped worldwide. Fairview also maintains a wide selection of other radio frequency twinaxial and coaxial cable types that ship same-day from our warehouse as with the rest of our other RF/microwave and millimeter wave components.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		8	GHz
Cutoff Frequency		39		GHz
Impedance		50		Ohms
Velocity of Propagation		83		%
Time Delay		1.22 [4]		ns/ft [ns/m]
Shielding Effectiveness	90			dB
Dielectric Withstanding Voltage (DC)			1,000	Vdc
Jacket Spark			3,000	Vrms
Inner Conductor DC Resistance			5.36	Ohms/1000ft

^{*} LMR™ is a trademark of Times Microwave Systems.



Times Microwave LMR-200 Low Loss Flexible Coax Cable Black PE Jacket



LMR-200

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Outer Conductor DC Resistance			4.9	Ohms/1000ft
Nominal Capacitance		24.5 [80.38]		pF/ft [pF/m]
Nominal Inductance		0.061 [0.2]		uH/ft [uH/m]
Input Power (Peak)			2.5	kWatts

Performance by Frequency Band

Description	F1	F2	F3	F4	F5	Units
Frequency	50	150	220	450	900	MHz
Attenuation, Typ	2.3	4	4.8	7	9.9	dB/100ft
	7.55	13.12	15.75	22.97	32.48	dB/100m
Input Power (CW), Max	790	450	370	260	180	Watts

Description	F6	F7	F8	F9	F10	Units
Frequency	1.5	1.8	2	2.5	5.8	GHz
Attenuation, Typ	12.9	14.2	15	16.9	26.4	dB/100ft
	42.32	46.59	49.21	55.45	86.61	dB/100m
Input Power (CW), Max	140	130	120	110	70	Watts

Mechanical Specifications

Diameter Weight

Min. Bend Radius (Installation)

Min. Bend Radius (Repeated)

Bending Moment Tensile Strength Flat Plate Crush 0.195 in [4.95 mm] 0.024 lbs/ft [0.04 kg/m] 0.5 in [12.7 mm] 2 in [50.8 mm] 0.2 lbs-ft [0.27 N-m]

40 lbs [18.14 kg] 15 lbs/in [0.27 kg/mm]

Construction Specifications

Description	Material and Plating	Diameter		
Inner Conductor	Copper, 1 Strand	0.044 in [1.12 mm]		
Conductor Type	Solid			
Dielectric	PE (F)	0.116 in [2.95 mm]		
First Shield	Aluminum Tape			
Second Shield	Tinned Copper Braid			
Jacket	PE, Black	0.195 in [4.95 mm]		



Times Microwave LMR-200 Low Loss Flexible Coax Cable Black PE Jacket



LMR-200

Environmental Specifications

Temperature

Operating Range -40 to 85 deg C Storage Range -70 to 85 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Times Microwave LMR-200 Low Loss Flexible Coax Cable Black PE Jacket from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Lewisville, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: Times Microwave LMR-200 Low Loss Flexible Coax Cable Black PE Jacket LMR-200

URL: https://www.fairviewmicrowave.com/lmr200-low-loss-flexible-coax-cable-pe-jacket-lmr-200-p.aspx

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to impliment improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume liability arising out of the use of any part or document.

